



NOTE: All relevant materials are complied with RoHS directive .

POSITION	A±0.3	B±0.2	C±0.2	D±0.2	E±0.2	F±0.2	G±0.2	H±0.1
9Pin	30.85	25.00	16.40	7.90	14.95	12.55	2.77	2.84
15Pin	39.25	33.35	24.70	7.90	14.95	12.55	2.77	2.84
19Pin	44.80	38.86	30.00	7.90	14.95	12.55	2.77	2.84
23Pin	50.30	44.30	35.30	7.90	14.95	12.55	2.77	2.84
25Pin	53.10	47.04	38.52	7.90	14.95	12.55	2.77	2.84
37Pin	69.40	63.50	54.85	7.90	14.95	12.55	2.77	2.84
50Pin	67.08	61.05	52.25	10.90	14.95	15.37	2.77	2.84

ELECTRICAL CHARACTERISTICS:
 CONTACT CURRENT RATING:1AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE:AC 500V R.M.S
 INSULATION RESISTANCE:500 MEGOHMS MINIMUM
 AT DC 500V.
 CONTACT RESISTANCE:30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE:-40°C TO +70°C.

MATERIALS:
 CONTACTS:BRASS ,T=0.20 .
 INSULATOR:P.B.T.U.L 94V-0 RATED.
 SHELL:COLD ROLLED STEEL ,T=0.40 .

FINISHES:

CONTACT:GOLD FLASH
 SHELL:FRONT SHELL NICKEL PLATED
 REAR SHELL TIN PLATED
 PLASTIC:WHITE

MATING CYCLES:

9P, 15P AND 25P: 50 TIMES
 37P AND 50P: 20 TIMES