MATERIAL:
INSULATOR:PBT+30% GLASS FIBER(UL94V-0).
Terminal:Copper Alloy
CONTACPLATED:GOLD OVER NICKELOR TIN
SHELL:STEEL, nickel
SPESIFICATION:
CURRENT RATE:5 AMPS
INSULATOR RESISTANCE:1000M MIN.AT 500V DC
DIELLECTRIC STRENGTH:1000V PER
OPERTION TEMPERATURE:-55°C TO+105°C
IMPEDANCE:16W FOR 25MHz

ORDER INFORMATION

DBR1-MXX X B X X - L

◎:Standard Recommend

No, of contacts	◎GI:Gold Flash	SJ:Selective	BBlack Insulator	1:Fork grounding			LReHS + P,B,T
	GA:3u"	SA:3u"					
	GB:10u"	SB:10u"					
	GC:20u"	SC:20u"					
	GD:30u"	SD:30u"					

Dimensions

Positions	A	B	C
9	30.80	24.99	16.90
15	39.20	33.32	25.30
25	53.10	47.04	39.00
37	70.00	63.50	55.40



7.2mm Footprint



RECOMMENDED PC BORAD LAYOUT
APPLICATIONS: PC BOARD THICKNESS=1.60mm

AREA	REV.	DESCRIPTION	DATE
⚠	B	Delete the Tin Plating Options	

品名 TITLE	D-SUB RIGHT ANGLE TYPE 7.2mm MALE				
品號 PART NO.	DBR1-MXX-L			日期 DATE	2008/11/18
圖號 DRAWING NO.	DBR1-MXX-L	版本 REV.	B	繪圖 DRAWN	
客戶品號 CUSTOMER P/N		比例 SCALE	FREE	核對 CHECKED	
公差 TOLERANCE	.X ±0.20 .XX ±0.15	單位 UNIT	mm	核准 APPROVED	