



Designation IEC:

HR03

Size:.....
 Nominal Voltage:.....
 Rated Capacity:.....
 Internal Resistance DC; fully charged:.....
 Impedance AC at 1 kHz; fully charged:.....
 Max. Discharge Current (continuous load / 0.8 V):.....

AAA
1.2 V
800 mAh
90 mΩ
40 mΩ
1.6 A

Typical Capacity at:

0.2 C / 1.0 V:.....
 1.0 C / 0.9 V:.....

800 mAh
720 mAh

Dimensions:

Diameter a:.....
 Height b:.....
 Shoulder Height c:.....
 Cap Diameter d:.....
 Volume:.....
 Weight (approx.):.....

10.5^{-1.0} mm
44.5^{-1.2} mm
43.7^{-1.2} mm
3.8^{-1.8} mm
3.8 cm³
12 g

Charge Conditions at:

Standard Charge:.....
 Fast Charge:.....
 Trickle Charge (0.03 - 0.05 C):.....

80 mA, 16 h
800 mA (-dV)
24 - 40 mA

Temperatures (recommended / permissible) at:

Storage:.....
 Charge:.....
 Fast Charge:.....
 Discharge:.....

-20 °C ... 25 °C / -20 °C ... 40 °C
15 °C ... 30 °C / 0 °C ... 45 °C
15 °C ... 30 °C / 0 °C ... 40 °C
0 °C ... 40 °C / 0 °C ... 50 °C

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries