






			
Art. Nr.	± [mm]	R _{th} [K/W]	⊗	Art. Nr.	± [mm]	R _{th} [K/W]	⊗
FK 127 SA-3	12,7	8,0	TO 3	FK 127 SA	12,7	8,0	ohne
FK 191 SA-3	19,1	6,6	TO 3	FK 191 SA	19,1	6,6	ohne
FK 318 SA-3	31,8	4,8	TO 3	FK 318 SA	31,8	4,8	ohne
FK 254 SA-3	25,4	5,8	TO 3				

Material: Aluminium Druckguss
Oberfläche: schwarz lackiert

									
Art. Nr.	± [mm]	R _{th} [K/W]	⊗	Art. Nr.	± [mm]	R _{th} [K/W]	⊗		
FK 201 SA	25,4	6	ohne	FK 202 SA	12,7	8	ohne		
FK 201 SA 3	25,4	6	TO 3	FK 202 SA 3	12,7	8	TO 3		
FK 201 SA CB	25,4	6	CB	FK 202 SA CB	12,7	8	CB		

						
Art. Nr.	± [mm]	R _{th} [K/W]	⊗			
FK 205 SA L	31,8	9,0	L			
FK 206 SA L	25,4	10,5	L			
FK 207 SA L	19,1	12,0	L			
FK 208 SA L	12,7	14,0	L			

Material: Aluminium
Oberfläche: schwarz eloxiert

Aufsteckkühlkörper → C 10 – 14
Kleinkühlkörper für TO 5 und TO 18 → C 16 – 17
Kühlkörper für D PAK → C 19
Aluminiumoxydscheiben → E 9 – 10

Einpressniet
Kapton-Isolierscheiben
Silikonscheiben
Glimmerscheiben

→ E 37
→ E 8
→ E 2 – 4
→ E 11