









REV.	ECN	DESCRIPTION	APPROVED
A	YTXXXX	RELEASE TO CUSTOMER.	SKY 02/23/11

Electrical Characteristics:  
 Current rating: 0.4A AC/DC  
 Voltage rating: 50V AC/DC  
 Temperature range: -25°C~+85°C  
 Withstand Voltage: 200V AC/Minute  
 Contact Resistance: ≤ 20mΩ  
 Insulation resistance: ≥ 50 MΩ  
 Relative Humidity: 93%+40°C

Material Description:  
 Terminal: Phosphor Bronze Gold-plated  
 Fitting Nail: Brass Tin-plated  
 Housing: Thermoplastic(UL94V-0),COLOR:WHITE  
 Slider: Thermoplastic(UL94V-0)



SECTION A-A



Part No. Information:

5225. 2413. 2100

No. of Pins

Packing:

1=Tube

2=Tape&Reel with Mylar

3=Tape&Reel w/o Mylar



UNLESS OTHERWISE SPECIFIED TOLERANCES				UTE <sup>®</sup> YOUTE ELECTRONIC CO.,LTD			
.X	+/- 0.35	.X"	+/- 3.0"	CUSTOMER DRAWING			
.XX	+/- 0.25	.X"	+/- 2.0"				
.XXX	+/- 0.15	.XX"	+/- 1.0"				
DRAWING FILE :				TITLE		DESCRIPTION	
FOR MATERIALS AND FINISHES SEE NOTES				DRAWN		0.5mm FPC SMT Cover Lifting Type. Double contact	
PROJECTION				CHECKED		DRAWING NO.	
				APPROVED		5225. 2413. 2100	
						PART NO.	
						5225. 2413. 2100	
						REV.	
						A	
UNIT		MM		SCALE		NONE	
						SHEET 1 OF 1	