




A

**Abstandsbolzen und Distanzrollen**

B

**Distanzrollen**


C

D

E

F

G

H

I


K

L

M

N

Art. Nr.	Länge [mm]	Art. Nr.	Länge [mm]
<b>DR 081 V0</b>	1	<b>DR 813 V0</b>	13
<b>DR 082 V0</b>	2	<b>DR 814 V0</b>	14
<b>DR 083 V0</b>	3	<b>DR 815 V0</b>	15
<b>DR 084 V0</b>	4	<b>DR 820 V0</b>	20
<b>DR 085 V0</b>	5	<b>DR 825 V0</b>	25
<b>DR 086 V0</b>	6	<b>DR 830 V0</b>	30
<b>DR 087 V0</b>	7	<b>DR 835 V0</b>	35
<b>DR 088 V0</b>	8	<b>DR 840 V0</b>	40
<b>DR 089 V0</b>	9	<b>DR 845 V0</b>	45
<b>DR 810 V0</b>	10	<b>DR 850 V0</b>	50
<b>DR 811 V0</b>	11	<b>DR 860 V0</b>	60
<b>DR 812 V0</b>	12		



Art. Nr.	Länge [mm]	Art. Nr.	Länge [mm]
<b>DR 105 V0</b>	5	<b>DR 135 V0</b>	35
<b>DR 110 V0</b>	10	<b>DR 140 V0</b>	40
<b>DR 115 V0</b>	15	<b>DR 145 V0</b>	45
<b>DR 120 V0</b>	20	<b>DR 150 V0</b>	50
<b>DR 125 V0</b>	25	<b>DR 160 V0</b>	60
<b>DR 130 V0</b>	30		

**Sonderlängen auf Anfrage**

<b>Material</b>	Polyamid
<b>Wärmeformbeständigkeit</b>	180 °C
<b>Temperaturbereich</b>	+180 °C
<b>Farbe</b>	schwarz
<b>Brennbarkeitsklasse</b>	UL 94 V-0

**E 33**
**Lötstifte**  
**Lötstopper**  
**Miniatur Abstandsbolzen**  
**Montageteile für Kühlkörper**

 → E 36  
 → E 36  
 → E 26  
 → E 42 - 43

**Kühlkörper-Profilübersicht**  
**Leiterplattenkühler**  
**Sonderprofile**  
**Klammerbefestigung f. DIN-Schiene**

 → A 13 - 16  
 → A 89  
 → A 136  
 → E 16