


CREALITY BOX

Ouick Start Guide



Equipment Introduction





1 RJ45 port 6 Yellow light: WIFI working status 2 Connect printer/camera 7 Blue light: Ethernet indicator 13 Micro USB power socket ! 8 Green light: Cloud service or network configuration indicator 14 TF card connector 9 Red light: TF card indicator 5 Reset button 10 Power cable

2 Instructions

- 1. Insert the TE Card (FAT32 or exFAT formated) into the card connector
- 2. Connect the MINI/Micro USB socket of printer to the USB1/USB2 port of the box with USB cable.
- 3. Connect the end of the box power cable into the box Micro USB port, and then connect the other end to the power adapter.
- 4. Turn on the power switch of the printer.
- 5. Open the Android phone store, google play, apple store, etc., search for "Creality Cloud" to download the APP.
- 6. Open "Creality Cloud", click "Device" → "+". Scan the QR on the back of the box and name it, and configure the network according to the Creality Cloud cue phrases. When the box is online, you can enjoy printing remotely.

- 1. When the yellow light goes blinking, it means the box has started to work.
- 2. When the green light goes blinking, it means that the mobile phone network configuration information has been received, and the steady light means it is not connected to the cloud service.
- 3. When the red light is always on, it means that the TF card is not inserted

Notes: The output specification of the power adapter is 5V=2.4A (≥ 2A); after power on, if the box doesn't work normally due to the wrong configurations, you can press the reset button for over 5 seconds until the factory settings are restored, and then configure the network again in "Creality Cloud".



-mail: info@creality.com cs@creality.com













CREALITY BOX

快速入门指南



设备简介



1 RJ45网□	6 黄灯:WIFI工作状态
2 连接打印机/摄像头	7 蓝灯:以太网指示灯
3 Micro USB电源接口	8 绿灯:云端/配网指示灯
4 TF卡座	9 红灯:TF卡指示灯
5 复位按钮	10 电源线

2 操作说明

- 1、将 TF 卡 (FAT32/exFAT 格式) 插入盒子 TF 卡座处。
- 2、用打印机配套的 USB 通信线缆, 把打印机 MINI/Micro USB 端 口和盒子的 USB1/USB2 端口连接起来。
- 3、将盒子电源线一端插入盒子 Micro USB 接口,另一端连接电源

- 6.打开"创想云"APP.点击"设备"→"+".扫描盒子背面的二维码添 加对应盒子,并按"创想云"APP中引导配置网络,待盒子显示在线 后,即可使用 APP 远程打印。

- 1、黄灯闪烁时代表盒子已开始工作。
- 2、绿灯闪烁时代表已接收手机配网信息,常亮代表未连接到云端
- 3、红灯常亮时代表未插入TF卡。

注意: 电源适配器输出规格为 5V--2.4A(≥2A); 通电后, 如果 5 秒以上, 直至恢复出厂设置, 再用"创想云"APP 重新配网



□ 深圳市创想三维科技有限公司 深圳市龙华区大浪街道同胜社区金城工业园第三栋12









