

Spiral Hose

Item Code	80012.64220.29024
Description	36500 ALI-FLEX N/V 2" 20m 1bPLT
Flexible Material	Plasticized PVC
Rigid Material	Impact modified U-PVC
Marking	F/WW/YY (WW/FF= week and year of production)

Dimensional Data	Unit	Value	Test Method
Hose I.D.	mm	50	UNI EN ISO 4671
Hose O.D.	mm	57	UNI EN ISO 4671
Thickness:	mm	3,5	UNI EN ISO 4671
Weight:	g/m	600	---
Length:	m	20	UNI EN ISO 1307

Technical Specifications	Unit	Value	Test Method
WORKING PRESSURE AT 23 ± 2°C	bar	4	UNI EN ISO 1402
BURSTING PRESSURE AT 23 ± 2°C	bar	12	UNI EN ISO 1402
Vaccum	mH ₂ O	6	UNI EN ISO 7233
MIN BENDING RADIUS	mm	270	ISO 10619-1
WORKING TEMPERATURE	°C	-10/+55	Internal

Features

- Low pressure suction and delivery hose ideal for fountains and ponds
- Plasticized PVC flexible hose
- Rigid shock-resistant PVC reinforcement spiral
Smooth inside, corrugated outside

Material Compliances

- Reach (EC-REGULATION No.1907/2006)
- RoHS (2002/95/CE & 2011/65/CE & 2015/863)
- Phthalate free (<0,1%)