Product Data Sheet



Product picture: Product picture:	BOLD item code:	13849
Product picture: Affilities	Product name:	Solar-Tischleuchte IP44
Colour: Allik tea Operation: Sy7 (by L-ben rechargeable battery) ILED module: 1 50m, 50m (Colour temperature: Colour temperature: 2700K Colour temperature: Sy8 (Colour temperature: Sy8 (Brand:	BOLD LIGHTING
Operation: SYDC, 14 Day USB-C) 3,77 (by Liven rechargeable battery) Power consumption/lumen Max, 5,591, 100m LED module: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm white, non-replaceable) Solor panel: 1,6W, 160mr(15pcs SMD LED, warm	Product picture:	
Sylenation (Power Consumption (Jumen of whole light): LED module: 1	Colour:	Milk tea
of whole light." (M80.4.3-3.9.Y. (Journal LED module: 1.69/f. (80 mt 15pcs SMD LED, warm white, non-replaceable) Solar panel: 180 mA, 5V Colour rendering index (CRI): 95 Energy efficiency class: F Charging time: 8 bby solar, 4.5h by USB cable Run time: 6 hat highest brightness Run time: 6 hat highest brightness Class III Profection class: Class III Profection class: Class III Profection disas: Class III Profection genere: P44 Life time(L70850): 25000 h Operating temperature: 90°C to +45°C Dimmable: yes, via the touchravitch (long press for stepless dimming) Dimmable: Plastic Weight of the unit: Solar table lamp IP44, CRIS LED module: 1.6W/f.60lm 2700K Material: Plastic Detailed construction: Solar table lamp IP44, CRIS LED module: 1.6W/f.60lm 2700K Material: Plastic Concr mik tea Touch On-Orl, long press for Stepless Dimming Unit A.7 v.2000mAh, 1.8650 Li-on rentargeable battery (Indoor & outdoor use) Brown box with color sticker Color mix tea Touch On-Orl, long press for Stepless Dimming Unit A.7 v.2000mAh, 1.8650 Li-on rentargeable battery (Indoor & outdoor use) Brown box with color sticker EAN code: 4260663511619 Cuter carton size: 37.5X25.5X480CM Under carton size: 12x12x22CM	Operation:	5V/DC,1A (by USB-C) 3,7V (by Liion rechargeable battery)
Soler panel: Colour rendering index (CRI): Colour rendering index (CRI): Energy efficiency class: From time: 8 bity solar, 4.5h by USB cable Run time: 6 hat highest brightness Class III Protection deprese: Life time(L70850): Operating temperature: Or to +47° C Dimenable: Dimenable: Dimenable: Dimenable: Dimenable: Plastic Weight of the unit: Soler faible lamp IP44. CRIS LED module: 1.8W 160m 2700K Material: Soler faible lamp IP44. CRIS LED module: 1.8W 160m 1270K Material: Detailed construction: Detailed	of whole light:	Max.5.5W, 100lm
Colour temperature: Charging time: 8h by solar, 4.5h by USB cable Charging time: 6h at highest brightness Rechargeable battery: 1 x 3.7V DC. 2000mAh, L-lon, Type 18850, included, non-replaceable Safety protection diagree: 1 protection degree: 1 per protection degree: 2000 h Coperating temperature: 2000 h Coperating temperature: 2000 h Comerating temperature: 2000 h Comerating temperature: 2000 h Comerating temperature: 2000 h Comerating temperature: Plastic Weight of the unit: 1 Solar table lamp IP44, CRI95 LED module: 1,6W160im 2700K Color milk tea. Touch On/Off, long press for Stepless Dimming USB-C-charge port, with 1m USB cable with 1x3.7V 2000mAh, 1860 L-lon rechargeable battery (Indoor & outdoor use) Content of delivery: 1x Solar table lamp, 1x USB cable, 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511619 Cuter carton size: 37.5X25.5X4680CM Product Warrarty: 2 years		
Colour rendering index (CRI); 95 Energy difficiency class: F Charging time: B h by solar, 4.5h by USB cable Run time: 6h at highest brightness Rechargeable battery: 1 x3.7 V DC, 2000mAh, LHon, Type 18650, included, non-replaceable Safety protection class: Class III P protection degree: IP44 IVE timet(17650): 25000 h Operating temperature: 0°C to +45°C Storage temperature: vex. vex. vis. the touch switch (long press for stepless dimming) Dimensions: 0°115 x 203(H)mm Material: Plastic Weight of the unit: 1 Solar table lamp IP44, CRIB5 LED module: 1:6WH60m 2700K Material: plastic(ASAP-PC cover) Color: milk tea USB C-charep port, Win tim USB cable with 1x3.7V 2000mAh, 18650 Li-ion rechargeable battery (Indoor & outdoor sus/ with milk Scable with 1x3.7V 2000mAh, 18650 Li-ion rechargeable battery (Indoor & outdoor sicker EAN code: 4260683511619 Cuter carton size: 37.5X25.5X460CM User carton size: 37.5X25.5X460CM Loading qty per export 12 Product Warranty: 2 years		
Energy efficiency class: Charging line: 8h by solar, 4.5h by USB cable Run time: 6h at highest brightness Rechargeable battery: 1 x 3.7V DC, 2000mAh, Li-lon, Type 18650, included, non-replaceable Safety protection class: IP protection degree: IP4 Life time(I/T0850): 25000h Operating temperature: 20°C to +50°C Dimensions: Ø115 x 203(H)mm Ø116 x 203(H)mm Material: Plastic Weight of the unit: Safer table lamp IP44, CRI95 LED module: 1.6W/160lm 2700K Material: plastic(ABS+PC cover) Coir milk tea Touch On/Off, fong ress for Stepless Dimming USAC-charge port, with in USB cable with 1s.3 r/ 2000mAh, 18650 Li-on rechargeable battery (Indoor & contdoor vice) Concrated of delivery: 1.5Solar table lamp, 1x USB cable, 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511619 Cuter carton size: 37.5X25.5X460CM User carton size: 37.5X25.5X460CM LED module 1.0W/160 manual Product Warranty: 2 years		
Charging time: 8h by solar, 4.5h by USB cable Run tine: 6h at highest brightness Rechargeable battery: 1 x 3.7V DC, 2000mAh, LHon, Type 18650, included, non-replaceable Safety protection class: Class III P protection degree: P44 Life time(L70850): 25000 h Operating temperature: 0°C to +45°C Storage temperature: yes, via the touch switch (long press for stepless dimming) Dimensions: 0°115 x 203(H)mm Material: Plastic Weight of the unit: 1 Solar table lamp IPA4, CRISS LED module: 1-6W1/60m 2700K Clorr milk lea Touch On/Off, long press for Stepless Dimming USB-C-Charge port, with Inn USB cable with 1x3.7V 2000mAh, 18650 L1-ion rechargeable battery (Indoor & outdoor use) Package: Brown box with color sticker EAN code: 4280663511619 Cuter carton size: 37.5X25.5X460CM Cuter carton size: 12x12x22CM Laading qty per export 12 Product Warranty: 2 years		95
Ruchargeable battery: Rechargeable battery: 1 x 3.7 V DC, 2000mAh, Li-lon, Type 18650, included, non-replaceable Safety protection disas: (Protection degree: Life time(170850): Operating temperature: O°C to +45°C Storage temperature: -20°C to +55°C Dimmable: yes, via the touch switch (long press for stepless dimming) Dimensions: Ø115 x 203(H)mm Material: Plastic Weight of the unit: Solar table lamp IP44, CRIS5 LED module: 1,6WH 60im 2700K Material: plastic(ABS+PC cover) Detailed construction: Weight of the wide to the switch of the unit with 13.7 x 2000mAh, 18650 Li-lon rechargeable battery (Indoor & outdoor use) Detailed very: 1 x Solar table lamp, 1 x USB cable, 1 x instruction manual Package: Brown box with color sticker EAN code: 4260663511619 Outer carton size: 37.5x25.5x460CM Loading qty per export 12 Product Warranty: 2 years	Energy efficiency class:	F
Rechargeable battery: 1 x 3.7V DC, 2000mAh, L-Hon, Type 18650, included. non-replaceable Safety protection class: Class III Protection degree: [P44 Life time(.70850): 25000 h Operating temperature: O°C to +45° C Storage temperature: -20°C to +50° C Dimmable: yes, via the touch switch (long press for stepless dimming) Dimensions: Q115 x 203(H)mm Material: Plastic Weight of the unit: 1 Solar table lamp IP44, CRI95 LED module: 1.6W/160/lm 2700K Material psistic/ABS+PC cover) Color: milk tea Touch On/Off, long press for Stepless Dimming USB-C-charge port, with 1m USB cable with x2.7 V 200Mah, 168501-Hon rechargeable battery (Indoor & outdoor use) Content of delivery: 1xSolar table lamp, 1x USB cable, 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511619 Cuter carton size: 37.5X25.5X460CM Loading dty per export 12 Product Warranty: 2 years	Charging time:	8h by solar, 4.5h by USB cable
Safety protection class: IP protection degree: IP44 ILfe timet(TD850): Operating temperature: O°C to +50°C Dimmable: yes, via the touch switch (long press for stepless dimming) Dimensions: All 15 x 203(H)mm Material: Plastic Weight of the unit: Detailed construction: Detailed construction: Detailed construction: Detailed construction: Touch On/Off, long press for Stepless Dimming USB-C-charge port, with 1m USB cable with 15.37 v 2000mAh, 18650 Li-ion rechargeable battery (Indoor & outdoor use) Content of delivery: 1xSolar table lamp, 1x USB cable, 1x instruction manual Package: Brown box with color sticker EAN code: 220°C to +50°C Dimmable: 12x12x22CM Detailed construction: 12x12x2x2CM Detailed construction: 12x12x22CM Detailed construction: Detailed construction: 12x12x22CM Detailed construction: 12x12x22CM Detailed construction: Detailed construction: 12x12x22CM Detailed construction: Det	Run time:	6h at highest brightness
IP protection degree: IP44 Life time(170850): 25000 h Operating temperature: 200°C to +45°C Storage temperature: 200°C to +50°C Dimmable: yes, via the touch switch (long press for stepless dimming) Dimensions: Ø115 x 203(H)mm Material: Plastic Weight of the unit: 1	Rechargeable battery:	1 x 3.7V DC, 2000mAh, Li-lon, Type 18650, included, non-replaceable
Life time(L70850): 25000 h Operating temperature: 0°C to +45°C Storage temperature: yes, via the touch switch (long press for stepless dimming) Dimensions: 0715 x 203(H)mm Material: Plastic Weight of the unit: 1 Solar table lamp IP44, CRI95 LED module: 1.6W/160lm 2700k Material: Plastic USB-Caharge port, with rim USB cable with rim USB cable with rim 7.5 x 2010 count of delivery: 1xSolar table lamp, 1x USB cable, 1x instruction manual Package: Brown box with color sticker EAN code: 12x12x22CM Outer carton size: 37.5X25.5X460CM Leading qty per export 12 Product Warranty: 2 years	Safety protection class:	
Operating temperature: Storage temperature: -20°C to +50°C Dimmable: -yes, via the touch switch (long press for stepless dimming) Dimensions:	IP protection degree:	IP44
Storage temperature: -20°C to +50°C Dimmable: yes, via the touch switch (long press for stepless dimming) Dimensions: Ø115 x 203(H)mm Material: Plastic Weight of the unit: \ Solar table lamp IP44, CRI95 LED module: 1.6W1/160Im 2700K Material: plastic(ABS+PC cover) Color: milk tea Detailed construction: USB-C-charge port, with 1m USB-cable with 1x3.7V 200mAh, 18650 Li-ion rechargeable battery (Indoor & outdoor use) Content of delivery: 1xSolar table lamp, 1x USB cable, 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511619 Outer carton size: 37.5X25.5X460CM Uter carton size: 37.5X25.5X460CM Leading qty per export 12 Product Warranty: 2 years	Life time(L70B50):	25000 h
Dimensions:	Operating temperature:	0°C to +45° C
Dimensions: 2015 x 203(H)mm	Storage temperature:	-20°C to +50° C
Material: Plastic Weight of the unit: 1	Dimmable:	yes, via the touch switch (long press for stepless dimming)
Weight of the unit: Solar table lamp IP44, CRI95 LED module: 1.6W/160lm 2700K Material: plastic/ABS+PC cover) Color: milk tea Touch On/Off, long press for Stepless Dimming USB-C-charge port, with 1m USB cable with 1x3.7V 2000mAh, 18650 Li-ion rechargeable battery (Indoor & outdoor use)	Dimensions:	Ø115 x 203(H)mm
Solar table lamp HA4, CRISS LED module: 16W1/60Im 2700K Material: plastic (ABS+PC cover) Color: milk tea Touch On/Off, long press for Stepless Dimming USB-Coharge port, with fm USB cable with 1x3.7v 2000mAh, 18650 Li-ion rechargeable battery (Indoor & outdoor use) Content of delivery: 1xSolar table lamp, 1x USB cable, 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511619 Sale packaging size: 12x12x22CM Outer carton size: 37.5X25.5X460CM Loading qty per export 12 Product Warranty: 2 years	Material:	Plastic
LED module: 1.6W/160lm 2700K Material: plastic/ABS+PC cover) Color: milk tea Touch On/Off, long press for Stepless Dimming USB-C charge port, with 1m USB cable with 1x3.7V 2000mAh, 18650 Li-ion rechargeable battery (Indoor & outdoor use) Content of delivery: 1xSolar table lamp, 1x USB cable, 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511619 Sale packaging size: 12x12x22CM Outer carton size: 37.5X25.5X460CM Loading qty per export 12 Product Warranty: 2 years	Weight of the unit:	\
Package: Brown box with color sticker EAN code: 4260663511619 Sale packaging size: 12x12x22CM Outer carton size: 37.5x25.5x460CM Loading qty per export 12 Product Warranty: 2 years	Detailed construction:	LED module: 1.6W/160lm 2700K Material: plastic(ABS+PC cover) Color: milk tea Touch On/Off, long press for Stepless Dimming USB-C charge port, with 1m USB cable with 1x3.7V 2000mAh, 18650 Li-ion rechargeable battery
Package: Brown box with color sticker EAN code: 4260663511619 Sale packaging size: 12x12x22CM Outer carton size: 37.5x25.5x460CM Loading qty per export 12 Product Warranty: 2 years	Content of delivery:	1xSolar table lamp 1x USR cable 1x instruction manual
EAN code: 4260663511619 Sale packaging size: 12x12x22CM January Code Outer carton size: 37.5x25.5x460CM Loading qty per export 12 Product Warranty: 2 years		
Sale packaging size: 12x12x22CM Outer carton size: 37.5x25.5x460CM Loading qty per export 12 Product Warranty: 2 years	<u> </u>	
Outer carton size: 37.5X25.5X460CM 37.	Sale packaging size:	
Product Warranty: 2 years	Outer carton size:	37.5X25.5X460CM
	Loading qty per export	12
	Product Warranty:	2 years
Remarks: This product contains a light source of energy efficiency class F.		This product contains a light source of energy efficiency class F.