## **Product Data Sheet**



Product picture:    Soar wall lamp   Pi-4 with PiR	BOLD item code:	13843
Product picture:  Colour:  Operation:  USB-C: 597 DC, 1A 3,77 (Li-on rechargación battery)  Power consumption lumen of victo eligit  LED modulo:  Signa, 377 (Li-on rechargación battery)  Aby. 400m; 35pcs SMD LED, suem white, non-replacación;  Colour remorrary (Line)  Colour remorrary (Line)  Colour remorrary (Line)  Signa, 400m;  Signa,		
Product picture:  Colour:  Quantification:  Quantificatio		
Operation:  JUSB-C. SWI DC. 1A J. YU.Li-on rechangeable battery)  Power concumption lumen  Max. 5W, 180lm  280mA, 5W  Color prediction  280mA, 5W  Color predicting index (CRI)  Color underling index (CRI)  Color undex (CRI)  Color underling index (CRI)  Color undex (CRI)  Co		0
Sperior consumption fumen of whole light:  LED mediale:  45W, 400/m(3)pos SMD LED, warm white, non-replaceable)  Solar panel:  Colour temperature:  3000K  Colour temperature:  3000K  Colour temperature:  3000K  Colour temperature:  45 May 400/m(3)pos SMD LED, warm white, non-replaceable)  81 by solar, 4.5 by USB cable  Ran time:  256h at lowestbrightness (In mode I), 220 times defection (In mode II)  Rechargeable battery:  41 x 3.7 V DC, 2000mAn, LHon, Type 18650, included, non-replaceable  31 protection degree:  124  125 may 12	Colour:	gun grey
of whole light:   wide.cvr, rount   LED module:   4.5%, 4.00lm( 33pcs SMD LED, warm white, non-replaceable)   Solar panel:   250mA, 5V	Operation:	
Solar panel:  Colour temperature:  3000K  Colour temperature:  3000K  Colour temperature:  3000K  Colour temperature:  3000K  Colour temperature:  38 hb ys solar, 4.5h by USB cable  Run time:  355h at lowest brightness (in mode II);  Rachargeable battery:  1 x 3.7V DC, 2000mAh, LHon, Type 18650, included, non-replaceable  31 x 3.7V DC, 2000mAh, LHon, Type 18650, included, non-replaceable  31 x 3.7V DC, 2000mAh, LHon, Type 18650, included, non-replaceable  32 protection degree:  12 protection degree:  12 protection degree:  13 protection degree:  14 protection degree:  25 protection degree:  26 protection degree:  27 protection degree:  27 protection degree:  27 protection degree:  28 protection degree:  29 protection degree:  20 protection degree:  21 protection degree:  22 protection degree:  23 protection degree:  24 protection degree:  25 protection degree:  26 protection degree:  26 protection degree:  27 protection degree:  28 protection degree:  29 protection degree:  20 protection degree:  21 protection degree:  22 protection degree:  23 protection degree:  24 protection degree:  25 protection degree:  26 protection degree:  27 protection degree:  27 protection degree:  28 protection degree:  28 protection degree:  29 protection degree:  20 protection degree:	of whole light:	
Colour rendering index (CRI): 95 Colour rendering index (CRI): 95 Run time: 86 bity solar, 4.5h by USB cable Run time: 255h at lowestbrightness (in mode I), 220 times detection (in mode II) Run time: 925h at lowestbrightness (in mode I), 220 times detection (in mode II) Run time: 925h at lowestbrightness (in mode I), 220 times detection (in mode II) Run time: 925h at lowestbrightness (in mode I), 220 times detection (in mode II) Run time: 925h at lowestbrightness (in mode I), 220 times detection (in mode II) Run time: 925h at lowestbrightness (in mode		
Colour rendering index (CRI): 95 Charging time: 8h by solar, 4.5h by USB cable Run time: 255h at lowestbrightness (in mode I), 220 times detection (in mode II) Rechargeable battery: 1 x 3.7V DC, 2000mAh, LHon, Type 18650, included, non-replaceable Safety protection class: 1 IP protection degree: IP44 Life time(L70850): 25000 h Operating temperature: 0°C to +45°C Storage temperature: 2°C°C to +50°C Dimmable: N Dimmable: N Dimmable: N Dimmable: Plastic, Aurinium and steel Weight of the unit: 33g Solar wall amp IP44 with PIIR black sensor, CRID (COIM) 418 Back 2 working mode & Sensor mode with type-C charging port, no USB cable with 1x3 TV, 2000mAh, 18550 LHon rechargeable battery Twilight sensor (Turn on at dusk only) Package: Brown box with color siker EAN code: 4260663511657  Cuter carton size: 49.5X31.5X34CM  Loading gly per export 12 Product Warranty: 2 years	<del> </del>	
Charging time:  8h by solar, 4,5h by USB cable Run time: 255h at lowestbrightness (in mode II), 220 times detection (in mode II) Rechargeable battery: 1 x 3.7 V DC, 2000mAh, LHon, Type 18650, included, non-replaceable Safety protection class: Class III Pip rotection degree: Life time(L70850): 25000 h Operating temperature: 0°C to +45° C Storage temperature: No Dimensions: 0°130 x 207(H)mm Material: Weight of the unit: 339g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module 4, 59V/400im 3000K material/Aumnum-15teet-Plastic(AS+PC) Content of delivery: 2016 and the content of delivery: Twilight sensor (Turn on at dusk only) Package: Brown box with color striker EAN code: 49,5X31.5X34CM  Cuter carton size: 49,5X31.5X34CM  Cuter carton size: 49,5X31.5X34CM  Loading gtyper export 12 Product Warranty: 2 years	· · · · · · · · · · · · · · · · · · ·	
Run time:		
Rechargeable battery:  Safety protection class:  Class III  Protection degree:  IP44  Life time(I70B50):  25000 h  Core tang temperature:  Jor'C to +45° C  Storage temperature:  Jor'C to +50° C  Dimmable:  No  Material:  Plastic, Aluminum and steel  Weight of the unit:  Solg  Solar wall lamp IP44 with PIR  black sensor, (PSI65  LED module 4, 5W400/lm 3000K  material-Aluminum-Steel+Plastic(ABS+PC)  Color: Matt Black  Color: Matt Black  Uerking mode & Sensor mode  with type-C charging port, no USB cable with 1x3.7V, 2000mAh, 18650 Li-lon rechargeable battery  Timight sensor (Turi on at dusk only)  Content of delivery:  1x Product 2x fixing screws, 2x dowels, 1x Allen key, 1x Operation manual  Package:  Brown box with color sticker  EAN code:  49.5X31.5X34CM  Uer carton size:  49.5X31.5X34CM  Loading dty per export  12  Product Warranty:  2 years		* * *
Safety protection classs:    P protection degrees   P44		
IP protection degree:   IP44		
Upte time(L70850): 25000 h Operating temperature: 0°C to +45°C Storage temperature: 2°C°C to +50°C Dimmable: No Dimensions: 3130 x 207(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 539g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module 4, 54/400lm 3000K material-Aluminum+Steet-Plastic(ABS+PC) Color: Matt Black 2 working modes: 2 working modes with type-C charging port, no USB cable with 13, 37/4, 2007mAn, 14650 Li-bor rechargeable battery Twilight sensor (Turn on at dusk only)  Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x Allen key, 1x Operation manual Package: Brown box with color sticker  EAN code: 426063511657  Outer carton size: 49.5X31.5X34CM  Upter carton size: 49.5X31.5X34CM  Loading qty per export 12 Product Warranty: 2 years	<del></del>	
Operating temperature:  OrC to +45°C Storage temperature:  20°C to +50°C Dimmable:  No Dimensions:  Ø130 x 207(H)mm Material:  Plastic, Aluminum and steel Weight of the unit:  S39 Solar wall lamp IP44 with PIR black sensor, CRI95 LED module 4.5W/400lm 3000K material: Aluminum-Steel Plastic(ABS+PC) Color: Matt Black 2 working mode & Sensor mode with type-C charging port, no USB cable with 1x3.7V, 2000mAh, 18650 LH on rechargeable battery Twilight sensor (Turn on at dusk only)  Content of delivery:  1x Product, 2x fixing screws, 2x dowels, 1x Allen key, 1x Operation manual  Package: Brown box with color sticker  EAN code:  49.5X31.5X34CM   49.5X31.5X34CM  Loading gty per export  12 Product Warranty: 2 years		
Storage temperature: -20°C to +50°C Dimmable: No Dimensions: 9130 x 207(H)mm  Material: Plastic, Aluminum and steel Weight of the unit: 539g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module 4.5W/400lm 3000K material-Aluminum+Steel+Plastic(ABS+PC) Color: Matt Black 2 working modes: 2 working modes: 2 working modes: 4 with type-C charging port, no USB cable with 13.77. 200mAh, 18650 Li-bor rechargeable battery Twilight sensor (Turn on at dusk only)  Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x Allen key, 1x Operation manual Package: Brown box with color sticker  EAN code: 4260663511657  Outer carton size: 49.5X31.5X34CM  Loading qtyper export 12 Product Warranty: 2 years		
Dimnable: No Dimnesions: 07130 x 207(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 5399 Solar wall lamp IP44 with PIR black sensor, CRI95 LED module 4.5W400lm 3000K material Luminum-Steel-Plastic(ABS+PC) Color Meth Black Color		
Dimensions: Ø130 x 207(H)mm Material: Plastic, Aluminum and steel  Weight of the unit: 539g  Solar wall lamp IP44 with PIR black sensor, CRI95 LED motule 4,5W/400lm, 3000K material Aluminum-Steel-Plastic(ABS+PC) Color: Matt Black 2 working mode & Sensor mode with type-C charging port, no USB cable with type-C charging port, no USB cable with type-C tharging series.  Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x Allen key, 1x Operation manual Package: Brown box with color sticker  EAN code: 4260663511657   Outer carton size: 49.5X31.5X34CM  Users and the series of t	Storage temperature:	
Material:  Weight of the unit:  539g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module 4,50W400Im 3000K material:Aluminum+Steel+Plastic(ABS+PC) Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode with type-C charging port, no USB cable with 13,37V,2000mAh,18650 Livon rechargeable battery Twilight sensor (Turn on at dusk only)  Content of delivery:  1x Product, 2x fixing screws, 2x dowels, 1x Allen key, 1x Operation manual  Package: Brown box with color sticker  EAN code:  4260663511657  Outer carton size:  49.5X31.5X34CM  James Material:  49.5X31.5X34CM  James Material:  Application of the unit:  Application	Dimmable:	
Weight of the unit:    Solar wall tamp IP44 with PIR	Dimensions:	
Solar wall lamp IP44 with PIR black sensor, CRI95 LED module 4.5W400lm 3000K material:Aluminum+Steel+Plastic(ABS+PC) Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode with type-C charging port, no USB cable with type-C charging port, no USB cable with type-C value of the color stucker Twilight sensor (Turn on at dusk only)  Content of delivery:  1x Product, 2x fixing screws, 2x dowels, 1x Allen key, 1x Operation manual Package: Brown box with color sticker  EAN code:  4260663511657  Sale packaging size:  16x15x16CM  Outer carton size:  49.5X31.5X34CM  Loading qty per export 12 Product Warranty: 2 years	Material:	Plastic, Aluminum and steel
Package: Brown box with color sticker  EAN code: 4260663511657  Sale packaging size: 16x15x16CM  Outer carton size: 49.5X31.5X34CM  Loading qty per export 12  Product Warranty: 2 years	-	Solar wall lamp IP44 with PIR black sensor, CRI95 LED module 4.5W/400lm 3000K material: Aluminum+Steel+Plastic(ABS+PC) Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode with type-C charging port, no USB cable with 1x3.7V, 2000mAh, 18650 Li-ion rechargeable battery
Package: Brown box with color sticker  EAN code: 4260663511657  Sale packaging size: 16x15x16CM  Outer carton size: 49.5X31.5X34CM  Loading qty per export 12  Product Warranty: 2 years	Content of delivery:	1x Product, 2xfixing screws, 2x dowels, 1x Allen key, 1x Operation manual
EAN code:  4260663511657  Sale packaging size:  16x15x16CM  Outer carton size:  49.5x31.5x34CM  John Market Company Co		
Sale packaging size:  16x15x16CM    Solid packaging size:   16x15x16CM   Solid packag		
Outer carton size:  49.5X31.5X34CM		100,100,100,100
Product Warranty: 2 years	Outer carton size:	49.5X31.5X34CM
	Loading qty per export	12
Normania.	Remarks:	