Product Data Sheet



| Product picture: OLD LIGHTING Colour: OLD gray Operation: Description: Operation: Oscillation: Operation: Oscillation: Operation: Oscillation: Operation: Operati | BOLD item code: | 13844 |
|--|------------------------|--|
| Colour: Calour: Cal | | |
| Colour | Brand: | BOLD LIGHTING |
| Operation: JSP-CC-SV DC-14 3,7V (Lorenzehargebale battery) Power consumption/lumen of whole light in order products and state of whole light in order products and state of the consumption/lumen of whole light in order products and state of the consumption of | Product picture: | |
| Sylenation (Julian et al., 1900) Jay (Li-lon rechargeable battery) Max.5W, 160lim Max.5W, 160lim Max.5W, 160lim Jay (Libon module) Jay (Libo | Colour: | Gun grey |
| of whole light: IED module: 4 My Adolmy 35pcs SMD LED. warm white, non-replaceable) Solar panel: 250mA, 5V Calcur rendering index (CRI): 95 Chesping filme: 8 Ph by solar, 4.5 h by USB cable Ran time: 250m at lowest brightness (in mode I), 220 times detection (in mode II) Rachargeable battery: 37 X 37 V DC, 2000mAh, LHon, Type 18850, included, non-replaceable 358fety protection class: 18 III IP protection degree: IP44 ILI def sime(I/DSB): 2000 h Operating temperature: 2070 to +45° C Storage temperature: 2070 to +45° C Dimmable: No Dimensions: 0130 x 207(PH)mm Material: Plastic, Aluminum and steel Weight of the unit: 1087g 2er S'est Solar walltamp IP44 with PIR includes 2x model 13843 Black sensor. CRISO Detailed construction: Detailed construction: Detailed construction: Detailed construction: 2er S'est Solar walltamp IP44 with PIR (includes 2x model 13843) Black sensor. CRISO Will this sensor. CRISO Will this sensor. CRISO Detailed construction: Detailed construction: 2er S'est Solar walltamp IP44 with PIR (includes 2x model 13843) Black sensor. CRISO Will this sensor. CRISO Color Matt Black 2 working modes: Lendy, Saving mode & Sensor mode with type-C charging port, nr. USB cable with type-C other grape port, nr. USB cable with type-C other grape port, nr. USB cable Will year of the view | Operation: | |
| Solar panel: Colour rempetature: 300K Colour rempetature: 31 x 3 7 V DC, 2000mAh, LHon, Type 18650, included, non-replaceable Safety protection class: IP protection degree: IP44 IP protection degree: IP45 IP protection degree: IP46 IP46 IP50B IP67 IP68 IP68 IP68 IP68 IP68 IP68 IP68 IP68 | of whole light: | |
| Colour rendering index (CRI): 95 Colour rendering index (CRI): 95 Colour rendering index (CRI): 95 Run time: 8b by solar, 4.5h by USB cable Run time: 255h at lowest brightness (in mode I), 220 times detection (in mode II) Run time: 255h at lowest brightness (in mode I), 220 times detection (in mode II) Safety protection class: Class III Protection degree: P144 Life time(70950): 25000 h Operating temperature: 0°C to +45°C Dimmable: No Dimmable: No Dimmable: P130 x 207(H)mm Material: P130 x 207(H)mm Detailed construction: 2 x 207 x | | |
| Colour rendering index (CRI): 95 Charging time: 8h by solar, 4.5h by USB cable Run time: 255h at lowestbrightness (in mode I), 220 times detection (in mode II) Rechargeable battery: 1 x 3.7 V DC, 2000mAh, Li-Hon, Type 18650, included, non-replaceable Safety protection class: Class III III (In sime(L/0850): 25000 h Operating temperature: 070 to +45° C Storage temperature: 20° to +50° C Dimensions: No Dimensions: No Dimensions: 0130 x 20′ (Hymn Material: Plastic, Aluminum and steel Weight of the unit: 1087g Weight of the unit: 1087g Black sensor, CRI95 Black sensor, CRI95 LED module 4.5W/400m 3000K material-Muminum-Steel Plestic(ABS+PC) Color: Mat Black 2 verking modes Sensor mode Energy Saving mode Sensor | | |
| Charging time: 8h by solar, 4.8 ht y USB cable Run time: 255h at lowest brightness (in mode i), 220 times detection (in mode ii) Rachargeable battery: 1 x 3.7 V DC, 2000mAn, LHon, Type 18600, included, non-replaceable Per protection class: Class III Per protection deprese: Life time(7,0950): 25000 h Coperating temperature: 20°C to +50°C Dimmables: No Dimmables: Of 30 x 207(H)mm Material: Weight of the unit: 1879 Detailed construction: Detailed construction: Detailed construction: Detailed construction: Detailed with type C charging port, no USB cable with 1x 3.7 x, 2000mAn, 19650 Lion rechargeable battery Twillight sensor (7,000mAn, 19650 Lion rechargeable battery) Twillight sensor (7,000m and druss or with 1900m and a fusion or with 1900m and 1900m | | |
| Run time: 255h at lowestbrightness (In mode I), 220 times detection (In mode II) 1 x 3.7 V DC 2000mAh, Li-lon, Type 18650, included, non-replaceable 2560 | | |
| Rechargeable battery: Safety protection class: Class III Protection degree: IP44 Life time(L70850): 25000 h Operating temperature: Storage temperature: No Dimensions: Olass III No Detailed construction: Detailed | | |
| Safety protection class: IP protection degree: IP44 Life timet(176850): Operating temperature: OPC to +45°C Storage temperature: No Dimensions: Of 30 x 207(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 1087g 2er Set Solar wall tamp IP44 with PIR Includes 2x model 13843 Black sensor, CRISE COOR with protection: Coor Mat Black 2 working mode & Sensor mode with type-C charging port, no USB cable with 13, 37V, 2000-Mh, 18550 Libon rechargeable battery Twilight sensor (Turn on at dusk only) Content of delivery: 2x Product, 4x fixing screws, 4x dowels, 2x Allen key, 1x Operation manual Package: EAN code: 4260663511664 Cuter carton size: 60X32,5X27,5CM Coaling gtyper export 8 Product Warranty: 2 years | | |
| IP protection degree: IP44 | | |
| Life time(L70850): Operating temperature: O°C to +45°C Storage temperature: No Dimensions: O130 x 207(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 1087g Zer Set Solar wall ramp IP44 with PIR Includes 2x model 13843 Black sensor, CRISIO ELED module 4.5W/400fm 3000K material Aluminum*Steel+Plastic(ABS+PC) Color: Matt Black Covering modes: Element of behavior of b | | |
| Operating temperature: Storage temperature: -20°C to +45°C Storage temperature: -20°C to +55°C Dimmable: No Dimensions: Ø130 x 20°C thylmm Material: Plastic, Aluminum and steel Weight of the unit: 1087g Zer Set Solar wall lamp IP44 with PIIR Includes 2x model 13843 Black sensor, CRI95 LED module 4.5W400im 3000K material-Xburninum-Steel+Plastic(ABS+PC) Coir Matt Black 2 working modes: Energy Saving mode 8. Sensor mode with type-0-changing poin to USB cable with 1x3.7%, 2000mAin, 1650 Lbon rechargeable battery Twilight sensor (Turn on at dusk only) Content of delivery: 2x Product, 4x fixing screws, 4x dowels, 2x Allen key, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511664 Outer carton size: 60X32.5X27.5CM Loading dty per export 6 Product Warranty: 2 years | | |
| Storage temperature: 20°C to +50°C Dimmable: No Dimensions: Ø130 x 20°(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 22° Set Solar wall lamp IP42 with PIR Block songer, CRI95 LED module 4,544/A00lm Slock songer, CRI95 LED | | |
| Dimensions: Otion x 207(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 1087g EVEN ST Solar wall lamp IP44 with PIR Includes 2x model 13843 Black sensor, CRI95 LED module 4 5W/400lm 3000K material: Detailed construction: Detailed construction: Outer carton size: Outer carton size: 60X32.5X27.5CM Dimensions: Outer carton size: 60X32.5X27.5CM Discrept Stolar wall lamp IP44 with PIR Includes 2x model 13843 Black sensor, CRI95 LED module 4 5W/400lm 3000K material: EVENT STOLAR STOLA | | -20°C to +50°C |
| Material: Weight of the unit: 1087g Zer Set Solar wall lamp IP44 with PIR Includes 2xmodel 13843 Black sensor, CRI95 LED module 4.5W/400im 3000K material:Aluminum-Steel+Plastic(ABS+PC) Color: Mat Black Zer Saving mode & Sensor mode with type-Coloring port, no USB cable with 1x3.7V, 200m/kn, 18550 Lion rechargeable battery Twilight sensor (Turn on al totak only) Content of delivery: 2x Product, 4x fixing screws, 4x dowels, 2x Allen key, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511664 Outer carton size: 60X32.5X27.5CM User carton size: 60X32.5X27.5CM Loading qty per export 6 Product Warranty: 2 years | | No |
| Weight of the unit: 1087g 2er Set Solar wall lamp IP44 with PIR Includes 2x model 13843 Black sensor, CRISS LED module 4.5W/400lm 3000K material Aluminum+Steel+Plastic(ABS+PC) Coor: Matt Black 2 working modes: 2 working modes: with tyse-C charging bot, no USB cable with tys-C valoum, 18550 Li-ion rechargeable battery Twilight sensor (Turn on at dusk only) Content of delivery: 2x Product, 4x fixing screws, 4x dowels, 2x Allen key, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511664 Outer carton size: 60X32.5X27.5CM Loading qty per export 6 Product Warranty: 2 years | Dimensions: | Ø130 x 207(H)mm |
| Zer Sel Solar will lamp IP44 with PIR Includes 2x model 13843 Black sensor, CRI95 LED module 4.5W400im 3000K material:Aluminum-Steel+Plastic(ABS+PC) Color: Mat Black St. Sensor mode with 1yee Centeriang port, no USB cable with 1yee Cent | Material: | Plastic, Aluminum and steel |
| Includes 2x model 13443 Black sensor, CRI95 LED module 4.5W/400lm 3000K material x Munimum+Steel+Plastic(ABS+PC) Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode with type-C charging port, no USB cable with 1x3.7V, 2000mAh,18650 Li-lon rechargeable battery Twilight sensor (Turn on at dusk only) Content of delivery: 2x Product, 4x fixing screws, 4x dowels, 2x Allen key, 1x Operation manual Prackage: Brown box with color sticker EAN code: 4260663511664 Outer carton size: 60X32.5X27.5CM Loading dy per export 6 Product Warranty: 2 years | Weight of the unit: | 1087g |
| Package: Brown box with color sticker EAN code: 4260663511664 Sale packaging size: 19.5x15.5x25.5CM Outer carton size: 60X32.5X27.5CM Loading qty per export 6 Product Warranty: 2 years | Detailed construction: | Includes 2x model 13843 Black sensor, CRI95 LED module 4.5W/400lm 3000K material:Aluminum+Steel+Plastic(ABS+PC) Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode with type-C charging port, no USB cable with 1x3.7V, 2000mAh,18650 Li-ion rechargeable battery |
| Package: Brown box with color sticker EAN code: 4260663511664 Sale packaging size: 19.5x15.5x25.5CM Outer carton size: 60X32.5X27.5CM Loading qty per export 6 Product Warranty: 2 years | Content of delivery: | 2x Product Axiiving ecrave Ax dowele 2x Allenkey 1x Operation manual |
| EAN code: 4260663511664 Sale packaging size: 19.5x15.5x25.5CM Outer carton size: 60X32.5x27.5CM Loading qty per export 6 Product Warranty: 2 years | | |
| Sale packaging size: 19.5x15.5x25.5CM Outer carton size: 60X32.5X27.5CM Description: Consider the size of the | | |
| Loading qty per export 6 Product Warranty: 2 years | | 196X155X259AMA |
| Product Warranty: 2 years | Outer carton size: | |
| | Loading qty per export | 6 |
| Remarks: | Product Warranty: | 2 years |
| | Remarks: | |