Product Data Sheet



Product picture: Colour: Col	BOLD item code:	13846
Product picture: Colour: Operation: USB-C:SVI DC,1A SUPPLICATION Power consumption lumbs Ass SW, 1907, Lin Ass SW, 190		
Product picture: Colour: Colour: Construction: Contract of Colours: Col		
Operation: USS-C: SVI DC; 14 3,7% (Li-on rechargeable battery) Power consumption/lumen of whole light: LED module: 4,5W, 400(mt 33pcs SMD LED, warm white, non-replaceable) Solic panel: 2,50m, 4,50m, 5,50m, 9 Colour temperature: 3,000K 3,000K Colour temperature: 3,000K		
Operation: USS-C: SVI DC; 14 3,7% (Li-on rechargeable battery) Power consumption/lumen of whole light: LED module: 4,5W, 400(mt 33pcs SMD LED, warm white, non-replaceable) Solic panel: 2,50m, 4,50m, 5,50m, 9 Colour temperature: 3,000K 3,000K Colour temperature: 3,000K	Colour:	Gun grey
Operation: 3,77 (Li-lon rechargeable battery) Power consumption/lumen of whole light: LED module: 4,004, 400/min 33pcs SMD LED, warm white, non-replaceable) Solar panel: 250mA, SV Colour modering index (CRI): 95 Changing time: 850 at lowest brightness (in mode II), 220 times detection (in mode II) Rechargeable battery: 1 x 3,77 DC, 200mAh, Li-lon, Type 18550, included, non-replaceable) 374 (Life time(L7085): 375 (Life tim		-
of whole light: Neth-Styr. Iounn LED module 4.6 My Ablimit 39cps SMD LED, warm white, non-replaceable) Solar panel: 250mA, 5V Colour rendering index (CRI): 95 Chapting Inne: 8h by solar, 4.5h by USB cable Run time: 255h at lowest brightness (in mode I), 220 times detection (in mode II) Rechargeable battery: 1 x 3.7V OC, 200mAh, LHon. Type 18650, included, non-replaceable Safety protection class: 184 Ille timed, 17650): 25000 h Operating temperature: 174	Operation:	
Solar panel: Colour rempetature: 300K Colour rempetature: 8h by solar, 4,5h by USB cable Run time: 255h at lowest brightness (in mode I), 220 times detection (in mode II) Rechargeable battery: 1 x 3 77 DC, 2000mAh, LHon, Type 18850, included, non-replaceable Safety protection class: IP protection degree: IP44 IP4		Max.5W, 180lm
Colour rendering index (CRI): 95 Colour rendering index (CRI): 95 Run time: 255h at lowestbrightness (in mode I), 220 times detection (in mode II) Run time: 255h at lowestbrightness (in mode I), 220 times detection (in mode II) Run time: 255h at lowestbrightness (in mode I), 220 times detection (in mode II) Run time: 255h at lowestbrightness (in mode II), 220 times detection (in mode II) Brachargeable battery: 1 x 37 V DC, 2000mAh, LHon, Type 18850, included, non-replaceable Class III Profection degree: 1944 Life time(L70850): 25000 h Operating temperature: 0°C to +49°C Dimensions: 0°130 x 501.7(H)mm Material: No Dimensions: 0°130 x 501.7(H)mm Material: Plastic, Alumnum and steel Weight of the unit: 919 Set of 2 Solar pathway lamp IP44 with PIR, 50cm height include 2x model 18945 LED module 4.5W400lm 3000K black sensor, CRI95 material: Alumnum +ABS+C Color Mat Black LED module 4.5W400lm 3000K black sensor, CRI95 material: Alumnum +ABS+C Color Mat Black 2 working modes a Sensor mode 2 with type C charging port, no USB cable with 1x 3.7V 2000mAh, type 18850, Li-ion rechargeable battery Twilight sensor (Turn on al dusk only) Content of delivery: 2x Product(13845), 8x fixing screws, 6x dowels, 2x earth spike, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511688 Froduct Warranty: 2 years		
Colour mendering index (CRI): 95 Charging time: 8h by solar; 4.5n by USB cable Run time: 255h at lowest brightness (in mode II), 220 times detection (in mode II) Rechargeable battery: 1 x 3.7 V DC; 2000mAh, LHon, Type 18850, included, non-replaceable Safety protection class: 1 IP protection degree: 1P44 Life time(L70B50): 25000 h Operating temperature: 20°C to +50°C Dimmable: No Dimmable: No Dimmable: No Dimmable: Plastic, Aluminum and steel Weight of the unit: 9193 Set of 2 Solar pathway lamp IP44 with PIR, 50cm height include 2x model 13846 Include 2x model 13846 Detailed construction: 2 virging mode 2 sensor mode 2 installation ways: Screwad 8 spike with 1yesC charging part, no USB cable with 1x 5.7 v 2000mAh, yee 16850, Li-ton rechargeable battery Tivilght sensor (Crun at duals cone) Content of delivery: 2x Froduct (13845) etc. Sale packaging size: 44.5x16x11.5CM Outer cardon size: 460x37.5x37CM Loading dyper export 6 Product Warranty: 2 years		
Charging time: 8h by solar, 4.5 h by USB cable Run times: 255h at lowest brightness (In mode I), 220 times detection (In mode II) Rachargeable battery: 1 x 3.7 v Dc, 200mAh, L-Hon, Type 18650, included, non-replaceable Gass III Per protection class: Class III Per protection class: 2500 h Operating temperature: 2500 h Operating temperature: 20°C to +50°C Dimmables: No Dimmables: No Dimmables: Plastic, Aluminum and steel Weight of the unit: 919g Set of 2 Solar pathway lamp IP44 with PIR, 50cm height include 2x model 1384 b LED module 4.5 wW400lm 3000K black sensor, CRI95 material: Aluminum-ABS+PC 2 working modes: Energy Saving mode & Sensor mode 2 installation ways: Screwed & gaike with type-C charging port, no USB cable with 1x 3.7 v 2000mAh, type 18650, Li-lon rechargeable battery Twilight sensor (Turn on at dusk only) Content of delivery: 2x Product(13845), 8x fixing screws, 8x dowels, 2x earth spike, 1x Operation manual Package: Brown box with color sticker EAN code: 426063311688 Outer cardon size: 460x37.5x37CM Loading gly per export 6 Product/Warranty: 2 years		
Run time: Seth at lowest brightness (In mode I), 220 times defection (In mode II) Rechargeable battery: 1 x 3.7V DC, 2000mAh, Li-lon, Type 18650, included, non-replaceable Class III IP protection degree: IP44 Life time(170850): 2000 h Operating temperature: O°C to +45°C Storage temperature: O°S to 45°C Dimmable: No Dimensions: O130 x 501.7(H)mm Material: Plastic, Aluminum and steel Weight of the unit: Set of 2 Solar pathway lamp IP44 with PIR, 50cm height include 2x model 13845. LED model 4.5W/400m 3000K black sensor, CRI95 material-Aluminum+ABS+PC Color. Matt Black 2 installation ways: Screwed 8, spike with 1 x 3.7V 2000mAh, byer 19650, Li-on rechargeable battery Twilight sensor (Turn on at dusk only) Package: Brown box with code: 4206683511688 Outer carton size: 460X37.5X37CM 460X37.5X37CM 460X37.5X37CM 5 x 2 years		
Rechangeable battery: Safety protection class: Class III Protection degree: IP44 Life time(L70B50): 25000 h Operating temperature: -20°C to +56°C Dimmables: No Dimensions: 0130 X 501.7(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 919 Set of 250ar pathway tamp IP44 with PIR, 50cm height include 2x model 13845 LED module 4.5W/400fm 3000K black sensor, CRISB material-Aluminum+ABS+PC Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode 2 Installation ways: Screwed & spike with 1,3 TV 2000mAh, pp e1865, Li-on mechangeable battery Twilight sensor (Turn on at dusk only) Content of delivery: 2x Product (13845) 6x fixing screws, 6x dowels, 2x earth spike, 1x Operation manual Package: Brown box with color sticker EAN code: 460X37.5X37CM 460X37.5X37CM 5 Product Warranby: 2 years		
Safety protection class: Protection degree: IP44		
IP protection degree: IP44		
Life time(L/T0850): Operating temperature: O'C to +45°C Operating temperature: O'C to +45°C Dimmable: No Dimensions: Otto 30 x 501.7(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 919g Set of 2 Solar pathway lamp IP44 with PIR, 50cm height include 2x model 13845 LED module 4.8/W40lom 3000K black sensor, CRI95 material-Aluminum+ABS+PC Color: Matt Black Unstallation ways: Screwed & spike with type-C charging port, no USS cable with 1x 3.7 v 2000mAnt, type 18650, Li-ton rechargeable battery Twilight sensor (Tum on at dusk only) Content of delivery: 2x Product(13845), 6x fixing screws, 6x dowels, 2x earth spike, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511688 446X37.5X37CM Loading qty per export 6 Product Warranty: 2 years		
Operating temperature: Storage temperature: -20°C to -45°C Storage temperature: -20°C to +50°C Dimmable: No Dimensions: Ø130 x 501.7(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 9199 Set of 2 Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model 15845 LED module -5 Mid Sofar pathway lamp IP44 with PIR, 50cm height include 2x model		
Storage temperature: 20°C to +50°C Dimmable: No Dimensions: Ø130 x 501.7(t))mm Material: Plastic, Aluminum and steel Weight of the unit: 919g Set of 2 Solar pathway lamp IP44 with PIR, 50cm height Include 2x model 13846 LED module 4.70/4/400m 3000K material-Aluminum ABS+PC Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode 2 tarsfallation ways: Screwed & spike with 13.77 v 200mAh,type 1865, U-ion rechargeable battery Twilight sensor (Turn on at dusk only) Content of delivery: Package: Brown box with color sticker EAN code: 4260663311688 445x16x11.5CM Outer carton size: 460X37.5X37CM Loading qty per export 6 Product Warranty: 2 years		
Dimmable: No Dimensions: Of 30 x 501.7(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 919g stef of 2 Solar pathway lamp IP44 with PIR, 50cm height include 2x model 13845 LED motule 4.594/400lm 3000K black sensor, CR195 mm arterial Aluminum ABS+PC Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode 2 installation ways: Screwed & spike with 1x3.7V 2000mAh, type 18650, Li-ion rechargeable battery Twilight sensor (Turn on at dusk only) Content of delivery: 2x Product(13845), 6x fixing screws, 6x dowels, 2x earth spike, 1x Operation manual Package: Brown box with color sticker EAN code: 426063311688 Outer carton size: 460X37.5X37CM Loading gtyper export 6 Product Warranty: 2 years		
Dimensions: Ø130 x 501.7(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 919g Set of 2 Solar pathway lamp IP44 with PIR, 50cm height include 2x model 13845 LED module 4.5W/400lm 3000K black sensor, CRI95 material-Aluminum+AB5+PC Color: Matt Black ey 2 working modes: Energy saving mode & Sensor mode 2 tristallation ways: Screwed & spike with type-C charging potr, no USB cable with x3.7V.2000mAh, type 18650, Li-lon rechargeable battery Twilight sensor (Turn on at dusk only) Content of delivery: 2x Product(13845), 6x fixing screws, 6x dowels, 2x earth spike, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511688 Outer carton size: 44.5x16x11.5CM Loading gity per export 6 Product Warranty: 2 years		
Material: Weight of the unit: 919g Set of 2 Solar pathway lamp IP44 with PIR, 50cm height Include 2x model 13845 LED module 4.5 WW400lm 3000K black sensor, CRI95 material. Aluminum+ABS+PC Color. Mat Black 2 working modes: Energy Saving mode & Sensor mode 2 installation ways. Screwed & spike with 1x3.7V 2000mAh, type 18650, LL-lon rechargeable battery Twilight sensor (Turn on at dusk only) Content of delivery: 2x Product(13845), 6x fixing screws, 6x dowels, 2x earth spike, 1x Operation manual Package: Brown box with color sticker EAN code: 44.5x16x11.5CM Outer carton size: 460X37.5X37CM 460X37.5X37CM Loading qty per export 6 Product Warranty: 2 years		
Weight of the unit: 919g Set of 2 Solar pathway lamp IP44 with PIR,50cm height include 2x model 13845 LED module 4.9W400lm 3000K black sensor, CR195 material.Aluminum+ABS+PC Coor. Matt Black 2 working modes: Energy saving mode & Sensor mode 2 installation ways. Screwed & spike with type-C charging pot, no USB cable with tys-70 2000mAh,type 18650, Li-lon rechargeable battery Twilight sensor (Turn on at dusk only) Content of delivery: 2x Product(13845), 6x fixing screws, 6x dowels, 2x earth spike, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511688 44.5x16x11.5CM Outer carton size: 460X37.5X37CM		
Set of 2 Solar pathway Jamp IP44 with PIR, 50cm height Include 2x model 13845 LED module 4.5W/400lm 3000K black sensor, CRI95 material:Aluminum+AB8+PC Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode 2 installation ways: Screwed & spike with type-C charging port, no USB cable with 1x3.7V 2000mAhl,type 18650, Li-lon rechargeable battery Twilight sensor (Turn on at dusk only) Content of delivery: 2x Product(13845), 6x fixing screws, 6x dowels, 2x earth spike, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511688 Outer carton size: 460X37.5X37CM 460X37.5X37CM Loading dy per export 6 Product Warranty: 2 years		
Package: Brown box with color sticker EAN code: 4260663511688 Sale packaging size: 44.5x16x11.5CM Outer carton size: 460X37.5X37CM Loading qty per export 6 Product Warranty: 2 years	Detailed construction:	Include 2x model 13845 LED module 4.5W/400lm 3000K black sensor, CRI95 material: Aluminum+ABS+PC Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode 2 installation ways: Screwed & spike with type-C charging port, no USB cable with 1x 3.7V 2000mAh,type 18650, Li-ion rechargeable battery
Package: Brown box with color sticker EAN code: 4260663511688 Sale packaging size: 44.5x16x11.5CM Outer carton size: 460X37.5X37CM Loading qty per export 6 Product Warranty: 2 years	Content of delivery:	2x Product(13845), 6x fixing screws, 6x dowels, 2x earth spike, 1x Operation manual
Sale packaging size: 44.5x16x11.5CM Outer carton size: 460X37.5X37CM Loading qty per export 6 Product Warranty: 2 years		
Sale packaging size: 44.5x16x11.5CM Outer carton size: 460X37.5X37CM July Company of the package of the pac	EAN code:	4260663511688
Outer carton size: 460X37.5X37CM The first depart of the first	Sale packaging size:	
Product Warranty: 2 years	Outer carton size:	460X37.5X37CM Some this state
	Loading qty per export	6
Remarks:	Product Warranty:	2 years
	Remarks:	