## **Product Data Sheet**



Product picture:    Colour:   Gun grey	BOLD item code:	13848
Product picture:  Colour:  Colour:  Sign gray  Sign C- SV DC 14  Sign (L- Hor nechargable battery)  Power consumption lumino of whole light:  Life Tradule:  1,597 (L- Hor nechargable battery)  Power consumption lumino of whole light:  1,597 (L- Hor nechargable battery)  Solice panel  1,597 (L- Hor nechargable)  Solice panel  1,597 (L- Hor nechargable battery)  1,597 (L- Hor nechargable battery)  Solice panel  1,597 (L- Hor nechargable battery)  Solice panel  1,597 (L- Hor nechargable battery)  1,597 (L- Hor nechargable)  1,597 (L- Hor nechargable		
Product picture:    Colour:   Gungrey		·
Operation: JSR-C_SV/DC_1A 3,7V(-Li-on rechargeable battery)  Power consumption lumen of whole light: LED module: 4.5W, 400m/ 3epcs SMD LED, warm white, non-replaceable)  Sater paniel: 380m, 5V Colour temperature: 3000K Colour emodering index (CRI): 3000K Colour emodering index (CRI): 3000K Colour paniel street in the stree		
Sylvanian (Characteristics)  Sylvanian (Chara	Colour:	Gun grey
of whole light:    West   Month   Mont	Operation:	
Soler preseture:  OOK Colour temperature: DOSOK Colour temperature: Soler production (CRI): Soler prod	of whole light:	
Colour rendering index (CRI) 95 Colour rendering index (CRI) 95 Run time: 8b by solar, 4.5h by USB cable Run time: 255h at lowest brightness (in mode I), 220 times detection (in mode II) Rechargeable battery: 1 x 77 VC, 200mAh, LHon, Type 18650, included, replaceable    Part		
Colour rendering index (CRI): 95 Charging time: 8h by solar, 4.5h by USB cable Run fame: 255h at lowest brightness (in mode I), 220 times detection (in mode II) Rechargeable battery: 1 x 3.7V DC, 200mAh, L Hon, Type 18650, included, replaceable Safety protection class: 1 IP protection degree: IP44 Life timeLT0850): 25000 h Operating temperature: 0°C to +45°C Storage temperature: 20°C to +50°C Dimmable: No Dimensions: 114 x 114 x 513(H)mm Material: 1937g Set of Zsolar pathway lights IP44 with PIR Include 2x model 13847 Black sensor, CRISS Model and Auminium Weight of the unit: 1937g Set of Zsolar pathway lights IP44 with PIR Include 2x model 13847 Black sensor, CRISS Model and Auminium (Auminium Version of Storage Sto		
Charging time:  8h by solar 4.5h by USB cable Run time:  255h at lowest brightness (in mode I), 220 times detection (in mode II) Rechargeable battery:  1 x 3.7 V DC, 2000mAh, L-Hon, Type 18650, included, replaceable  Class III Protection degree:  Life time(1/0850):  25000 h  Operating temperature:  O'C to +45° C  Dimmable:  No  Dimmable:  No  Dimmable:  Plastic and Aluminum  Material:  1307  Set of Zsolar pathway lights IP44 with PIR Include 2x model 1381 PI44 with PIR Include 3x model 1381 PI	<b>-</b>	
Run time:  Rechargeable battery:  1 x 3.7V DC, 2000mAh, L-Hon, Type 18650, included, replaceable  Safety protection class:  IP protection degree:  IP44  ILE time(t/19850):  2000th  Operating temperature:  0°C to +45°C  Storage temperature:  -2°C to +5°C  Dimmeble:  No  Dimmesions:  114 x 114 x 513(H)mm  Material:  Pastle and Aluminum  Weight of the unit:  1307g  Weight of the unit:  1307g  Biack sensor, CRI95  Biack sensor, CRI95  LED module 4.5W/4000lm 3000K  Material-Aluminum-Plastic(ABS+PC)  Color: Matt Black  Verifing modes: Energy Saving mode & Sensor mode  2 installation ways: Screwed & spike  with bye-C charging port (USB cable not included )  with 1x 3.7V 2000mAh, type 18650, Li-ion rechargeable battery  Twilight sensor (Turn on at dusk only)  Content of delivery:  2x Product, 8 krising screws, 8x dowels, 4x earth spike, 1x Operation manual  Package:  Brown box with color sticker  EAN code:  4200683511725  Cuter carton size:  60.5X39X27CM  Leading qty per export  6  Product Warranty:  2 years	<del> </del>	
Safety protection dass:    Protection degree:   IP44     Itel time(I/DSDS):   25000 h   Operating temperature:   0°C to +45°C     Storage temperature:   0°C to +45°C     Dimanable:   No     Dimanable:   No     Dimanable:   Pleastic and Aluminum     Weight of the unit:   1307g     Safet 2 Solar pathway lights IP44 with PIR     Include 2x model 13847     Black sensor, CRIS     Black sensor		≥55h at lowest brightness (In mode I), 220 times detection (In mode II)
Safety protection dass:    Protection degree:   IP44     Itel time(I/DSDS):   25000 h   Operating temperature:   0°C to +45°C     Storage temperature:   0°C to +45°C     Dimanable:   No     Dimanable:   No     Dimanable:   Pleastic and Aluminum     Weight of the unit:   1307g     Safet 2 Solar pathway lights IP44 with PIR     Include 2x model 13847     Black sensor, CRIS     Black sensor	<b>-</b>	
Life time(L70859): 25000 h Operating temperature: 0°C to +45°C Storage temperature: 0°C to +45°C Dimmable: No Dimensions: 114 x 114 x 513(H)mm Material: Plastic and Aluminum Weight of the unit: 1307g  Black sensor, CR195 LED module 4.5WH400lm 3000K Material-Aluminum+Plastic(ABS+PC) Color: Matt Black Detailed construction: 2 working modes: Energy Saving mode & Sensor mode 2 installation ways: Screwed & spike with type-C charging port (USB cable not included) with 1x3.77 2000mAh type 18650, Li-ion rechargeable battery Twilight sensor (Turn on at dusk only)  Content of delivery: 2x Product, 8x fixing screws, 8x dowels, 4x earth spike, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511725  Sale packaging size: 59x12.5x12.5CM  Cutler carton size: 60.5x39x27CM  Loading dtyper export 6 Product Warranty: 2 years		
Operating temperature:  -20°C to +45°C Storage temperature: -20°C to +45°C Dimmable: No Dimensions:	IP protection degree:	IP44
Storage temperature: -20°C to +50°C Dimmabile: No Dimmensions: 114 x 114 x 513(H)mm Material: Plastic and Aluminum Weight of the unit: 1307g Set of 2 solar pathway lights IP44 with PIR Include 2x model 13847 Black sensor, CRISOIm, 3000K Material-Aluminum-Plastic(ABS+PC) Color: Matt Black 2 working modes: Energy, Saving mode & Sensor mode 2 2 working modes: Energy, Saving mode & Sensor mode 2 2 with type-C changing port (USB cable not included ) with 1x 3.7 v 2000mAh, type 18650, Li-ion rechargeable battery Twilight sensor (Tum on at dusk only)  Content of delivery: 2x Product, 8x fixing screws, 8x dowels, 4x earth spike, 1x Operation manual Package: Brown box with color sticker  EAN code: 4260663511725  Outer carton size: 60.5X39X27CM  Loading qty per export 6 Product Warranty: 2 years	Life time(L70B50):	25000 h
Dimmable: No Dimensions: 114 x 114 x 513(H)mm Material: Plastic and Aluminum Weight of the unit: 3307g Set of 2 solar pathway lights IP44 with PIR Include 2x model 13847 Black sensor, CRI95 LED module 4 50W MOInt 3000K Representation: 2 vorking modes: Energy Saving mode & Sensor mode 2 installation ways: Screwed & spike with type-C charging port (USB cable not included ) with 14.3.7 V 2007MA, hype 18650, Li-lon rechargeable battery Twilight sensor (Tum on at dusk only)  Content of delivery: 2x Product, 8x fixing screws, 8x dowels, 4x earth spike, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511725  Sale packaging size: 59x12.5x12.5CM  Outer carton size: 60.5X39X27CM  Leading qty per export 8 Product Warranty: 2 years	Operating temperature:	0°C to +45° C
Dimensions: 114 x 114 x 513(H)mm Material: Plastic and Aluminum Weight of the unit: 1307g Set of 2 solar pathway lights IP44 with PIR Include 2x model 13847 Black sensor, CRI95 LED module 42 Model 13847 Content of delivery: 2 working modes: Energy Saving mode & Sensor mode 2 installation ways: Screwed & spike with type-C charging port (US5 cable not included ) with 1x3.7V 2000mAh, type 18550, Li-lon rechargeable battery Twilight sensor (Turn on at dusk only)  Content of delivery: 2x Product, 8x fixing screws, 8x dowels, 4x earth spike, 1x Operation manual Package: Brown box with color sticker  EAN code: 42606635117.25  Sale packaging size: 59x12.5x12.5CM  Outer carton size: 60.5x39x27CM  Loading qty per export 6 Product Warranty: 2 years		
Material:  Weight of the unit:  1307g Set of Z solar pathway lights IP44 with PIR Include Zx model 13847 Black sensor, CR195 LED module 4.5W/400im 3000K Material: Aluminum+Plastic(ABS+PC) Color: Matt Black 2 working mode se: Energy Saving mode & Sensor mode 2 installation ways: Screwed & spike with type-C charging port (USB cable not included) with 1x3.7V 2000mAh,type 18650, Li-ion rechargeable battery Twilight sensor (Turn on at dusk only)  Content of delivery:  2x Product, &x fixing screws, &x dowels, 4x earth spike, 1x Operation manual  Package: Brown box with color sticker  EAN code:  59x12.5x12.5CM  Outer carton size:  60.5X39X27CM  Loading dty per export 6 Product Warranty: 2 years	<b></b>	<u> </u>
Weight of the unit:  Set of 2 solar pathway lights IP44 with PIR Include 2x model 13847 Black sensor, CRI95 LED module 4.5w/W400lm 3000K Material-Aluminum+Plastic(ABS+PC) Color: Matt Black sensor (CRI95 1 sensor (Sary Saving modes: Energy Saving mode & Sensor mode 2 working modes: Energy Saving mode & Sensor mode 2 installation ways: Screwed & spike with type-C charging port (USB cable not included ) with 1x3.7x 2000mAht, bye 18650, Li-ion rechargeable battery Twilight sensor (Turn on at dusk only)  Content of delivery:  2x Product, &x fixing screws, &x dowels, 4x earth spike, 1x Operation manual  Package: Brown box with color sticker  EAN code:  4260663511725  Sale packaging size:  59x12.5x12.5CM  Outer carton size:  60.5x39x27CM  Loading dty per export 6 Product Warranty: 2 years		
Set of 2 solar pathway lights IP44 with PIR Include 2x model 13847 Black sensor, CRI95 LED module 4,50W400lm 3000K Material Aluminum+Plastic(ABS+PC) Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode 2 installation ways: Screwed & spike with type-C charging port (USB cable not included 1) with 1x3.7V 2000mAh,type 18650, Li-ion rechargeable battery Twilight sensor (Turn on at dusk only)  Content of delivery:  2x Product, 8x fixing screws, 8x dowels, 4x earth spike, 1x Operation manual  Package: Brown box with color sticker  EAN code:  4260663511725  Sale packaging size:  59x12.5x12.5CM  Outer carton size:  60.5X39X27CM  Laading dy per export 6 Product Warranty: 2 years		
with 1x 3.7V 2000mAh,type 18650, Li-ion rechargeable battery Twilight sensor (Turn on at dusk only)  Content of delivery:  2x Product, 8x fixing screws, 8x dowels, 4x earth spike, 1x Operation manual  Package:  Brown box with color sticker  EAN code:  4260663511725  Sale packaging size:  59x12.5x12.5CM  Outer carton size:  60.5x39x27CM  Content of delivery:  4260663511725  Solox125x125MM  Content of delivery:  60.5x39x27CM  Content of delivery:  4260663511725  Solox125x125MM  Content of delivery:  59x12.5x12.5CM  Content of delivery:  59x12.5x12.5x12.5CM  Content of delivery:  59x12.5x12.5x12.5x12.5x12.5x12.5x12.5x12.5	Detailed construction:	Include 2x model 13847 Black sensor, CRI95 LED module 4.5W/400lm 3000K Material:Aluminum+Plastic(ABS+PC) Color: Matt Black 2 working modes: Energy Saving mode & Sensor mode 2 installation ways: Screwed & spike
Package: Brown box with color sticker  EAN code: 4260663511725  Sale packaging size: 59x12.5x12.5CM  Outer carton size: 60.5X39X27CM  Loading qty per export 6  Product Warranty: 2 years	Content of delivery	with 1x 3.7V 2000mAh,type 18650, Li-ion rechargeable battery Twilight sensor (Turn on at dusk only)
EAN code:  4260663511725  Sale packaging size:  59x12.5x12.5CM  Solitors  Final Conference of the Conf		
Sale packaging size:  59x12.5x12.5CM  59x12.5x12.5CM  59x12.5x12.5CM  50x125x125x125x12  50x125x125x12  50x125x		
Loading qty per export 6 Product Warranty: 2 years		550X125X125MM
Product Warranty: 2 years		60.5X39X27CM  The first found in
Remarks:		2 years
Normanio.	Remarks:	