Product Data Sheet

BOLD

BOLD Diem code: 13851 Product name: Solar wall amp IP44 with PIR Brand: BOLD LIGHTING Product picture: Gun grey. Colour: Gun grey. Colour: Gun grey. Operation: USB-0: SVI DC.1A. S.77 (Li-ion rechargeable battery) Power consumption/ lume divide light of whole light of lig	
Brand: BOLD LIGHTING Product picture: Image: Construction of the picture of the pictu	
Product picture: Gun grey Colour: Gun grey Operation: USB-C: SV DC, 1A 3,7V (Li-ion rechargeable battery) Power consumption/lumen Power consumption/lumen Max. 3.5W, 220im LED module: 2.5W, 280im (33pcs SMD LED, warm white, non-replaceable) Solar ganel: 400mA, SV Colour: mediangin (ndex (CR)); 95 Solar ganel: Colour: mediangin (ndex (CR)); 95 Solar ganel: Calcust reperature: 240 times detection (in mode II), 300 times detection (in mode III), 500 times detection (in mode III) Run time: 240 times detection (in mode III), 300 times detection (in mode III) Run time: 240 times detection (in mode III), 300 times detection (in mode III) Safety protection dass: Class III IP protection dass: Class III IP protection dass: 23000 h Operating temperature: 07C to +50° C Dimensions: 173x160x151(H)mm Material: Plastic, Auminum and steel Weight of the unit: 339g Dimensions: US2-Charge port, NO USB cable Twing temperature: 200C to +50° C Dimensions: US2-Charge port, NO USB c	
Colour: Gun grey Operation: USB-c; 50/ DC; 1A 3,7V (Li-ion rechargeable battery) Power consumption/lume of whole light: Max. 3.5W, 220/m LED module: 2,5W, 280/m (33pcs SMD LED, warm while, non-replaceable) Solar panel: 400mA, 5V Colour rendering index (CRI); 95 5 Charging time: 8h by solar, 4.5h by USB cable Run time: 240 times detection (In mode I), 300 times detection (In mode II), 500 times detection (In mode II) Rechargeable battery: 1: x3.7V DC, 200mAh, Li-lon, Type 18650, included, non-replaceable Safety protection class: Class III IP protection class: Class III IP protection class: Class III IP protection degree: IP44 Life time(I/CBS0): 25000 h Operating temperature: -20°C to +45°C Storage temperature: -20°C to +50°C Dimmable: No D	
Operation: USB-C: 5V / DC; 1A 3,7V (L-ion rechargeable battery) Power consumption/lumen of whole light: Max. 3.5W, 220Im LED module: 2.5W, 280Im(33pcs SMD LED, warm white, non-replaceable) Solar panel: 400mA, 5V Colour temperature: 3000K Colour temperature: 3000K Colour rendering index (CRI): 95 Charging time: Bh by solar, 4.5h by USB cable Run time: 240 times detection (In mode 1), 300 times detection (In mode 1), 500 times detection (In mode 1)] Rechargeable battery: 1 x 3.7V DC, 2000mAh, LHon, Type 18650, included, non-replaceable Safety protection class: Class III IP protection degree: IP44 Life time(L70850): 25000 h Operating temperature: -20°C to +45° C Storage temperature: -20°C to +50° C Dimmable: No Dimmable: No Dimmable: No Dimmable: No Diack sensor, CRI95 LED module: 2.5W/R20Im 3000K material:AllyR20Im 3000K material:AllyR20Im 3000K material:AllyR20Im 300K material:AllyR20Im 300K Material degree and remotion to the file free of the sensor of tum on at dusk only) with 1x3.7V, 2020/mAh, 18650 Lion rechargeable battery	
Operating temperature: -20°C to +50° C Dimensions: 173x160x151(H)mm Of the leight -20°C to +50° C Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar game: -20°C to +50° C Contraction: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar game: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar game of the order game of the order for the	
of whole light: Mikes.Surv. 220III LED module: 2.5W, 280Im(33pcs SMD LED, warm white, non-replaceable) Solar panel: 400mA, SV Colour temperature: 3000K Colour rendering index (CRI): 95 Charging time: 8h by solar, 4.5h by USB cable Run time: 240 times detection (In mode I), 300 times detection (In mode III) Rechargeable battery: 1 x 3.7V DC, 2000mAh, LHon, Type 18650, included, non-replaceable Safety protection class: Class: III I'P protection degree: IP44 Life time(L70B50): 25000 h Operating temperature: -20°C to +50° C Dimmable: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar warllamp IP44 with PIR black sensor, CRI95 LED module: 250/200m 3000K material:Aluminum*Steel+plastic(ABS+PC) Color: gun grey New working modes! UB8-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh, 18650 Li+ion rechargeable battery Off. Pies 1 time. Ort:	
Solar panel: 400mA, 5V Colour temperature: 3000K Colour temperature: 3000K Colour temperature: 8h by solar, 4.5h by USB cable Run time: 8h by solar, 4.5h by USB cable Run time: 240 times detection (In mode I), 300 times detection (In mode II), 500 times detection (In mode III) Rechargeable battery: 1 x 3.7V DC, 2000mAh, Li-Ion, Type 18650, included, non-replaceable Safety protection class: Class III IP protection degree: IP44 Life time(L70B50): 25000 h Operating temperature: -20°C to +45° C Storage temperature: -20°C to +45° C Dimmable: No Dimmensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar wall tamp IP44 with PIR black sensor, CR195 LED module: 2.5W/280Im 3000K material:Aluminum+Steel+plastic(ABS+PC) Color; gur grey Indicater tight ref New working modes1 USB-c charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh, 18650 Lion rechargeable battery Indicater tight ref Content of delivery: 1x Product, 2xfixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual	
Colour temperature: 3000K Colour rendering index (CRI): 95 Charging time: 8h by solar, 4.5h by USB cable Run time: 240 times detection (In mode I), 300 times detection (In mode II), 500 times detection (In mode III) Rechargeable battery: 1 x 3.7V DC, 2000mAh, LHon, Type 18650, included, non-replaceable Safety protection class: Class III IP protection degree: IP44 Life time(L70850): 25000 h Operating temperature: -20°C to +45° C Storage temperature: -20°C to +50° C Dimmable: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 388g Solar wall tamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280Im 3000K material:Aluminum*Steel*plastic(ABS+PC) Color: gui grey Indicater light red of the unit red and and and and and and and and and an	
Colour rendering index (CRI): 95 Charging time: 8h by solar, 4.5h by USB cable Run time: 240 times detection (In mode II), 300 times detection (In mode II), 500 times detection (In mode III) Rechargeable battery: 1 x 3.7V DC, 2000mAh, Li-lon, Type 18650, included, non-replaceable Safety protection class: Class III IP protection degree: IP44 Life time(L70B50): 25000 h Operating temperature: -0°C to +45° C Storage temperature: -20°C to +50° C Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 399g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2,5W/280Im 3000K material:Aluminum*Steel+plastic(ABS+PC) Color: gun grey New working modes! USB-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x3.7V, 2000mAh, 18650 Li-ion rechargeable battery Indicate light red and green 03.3 Pwa+18ms givefil oucce Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749 Immediate light red Immediate light red	
Charging time: Bh by solar, 4.5h by USB cable Run time: 240 times detection (In mode I), 300 times detection (In mode II), 500 times detection (In mode III) Rechargeable battery: 1 x 3.7V DC, 2000mAh, Li-lon, Type 18650, included, non-replaceable Safety protection class: Class III IP protection degree: IP44 Life time(L70B50): 25000 h Operating temperature: -20°C to +45° C Storage temperature: -20°C to +50° C Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280Im 3000K material:Aluminum*steel+leal+black(ABS+PC) Color; gun grey New working modes! New working modes! USB-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh, 18650 Li-ion rechargeable battery Indicate light red are ref. of the set file are re	
Run time: 240 times detection (In mode I), 300 times detection (In mode II), 500 times detection (In mode III) Rechargeable battery: 1 x 3.7V DC, 2000mAh, Li-lon, Type 18650, included, non-replaceable Safety protection class: Class III IIP protection degree: IP44 Life time(L70B50): 25000 h Operating temperature: -20°C to +45° C Storage temperature: -20°C to +50° C Dimmable: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280Im 3000K material:Aluminum+Steel+plastic(ABS+PC) Color: gun grey New working modes! USB-ccharge port, No USB cable With 1x 3.7V, 2000mAh, 18650 LHon rechargeable battery Uwith 1x 3.7V, 2000mAh, 18650 LHon rechargeable battery 0FF: Pres+1 time. Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749	
Rechargeable battery: 1 x 3.7V DC, 2000mAh, LHon, Type 18650, included, non-replaceable Safety protection class: Class III IP protection degree: IP44 Life time(L70B50): 25000 h Operating temperature: -20°C to +45° C Storage temperature: -20°C to +50° C Dimmable: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Detailed construction: Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280Im 3000K material:Aluminum+Steel+plastic(ABS+PC) Color: gun grey Indicator light red black sensor, CRI95 New working modes! USB-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh, 18650 LHon rechargeable battery Indicator light green OFF: Pres +1 line. doi: 0FF: Pres +1 line. Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749 Interational color sticker	
Safety protection class: Class III IP protection degree: IP44 Life time(L70B50): 25000 h Operating temperature: 0°C to +45° C Storage temperature: -20°C to +50° C Dimmable: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Detailed construction: Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280lm 3000K material:Aluminum+Steel+plastic(ABS+PC) Color: gun grey New working modes! Indicate light red and gree n VSE Prove 1 line stard. Detailed construction: USB-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh, 18650 Li-ion rechargeable battery Indicator light red and gree n VSE Prese + 1 sense. Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749	
IP protection degree: IP44 Life time(L70B50): 25000 h Operating temperature: 0°C to +45° C Storage temperature: -20°C to +50° C Dimmable: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Detailed construction: Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280lm 3000K material:Aluminum-Steel+plastic(ABS+PC) Color: gun grey Indicator light red and gree n New working modes! USB-C charge port, No USB cable Indicator light green with 1x 3.7V, 2000mAh, 18650 Li-ion rechargeable battery Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749	
Life time(L70B50): 25000 h Operating temperature: 0°C to +45°C Storage temperature: -20°C to +50°C Dimmable: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280Im 3000K matterial:Aluminum*Steel+plastic(ABS+PC) Color: gun grey New working modes! USB-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh,18650 Li-ion rechargeable battery OFF. Pres +1 time. Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code:	
Operating temperature: 0°C to +45° C Storage temperature: -20°C to +50° C Dimmable: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280Im 3000K material:Aluminum+Steel+plastic(ABS+PC) Color: gun grey New working modes! Indicator light red and green in New working modes! Detailed construction: USB-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh,18650 Li-ion rechargeable battery Indicator light green Rest working screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749	
Storage temperature: -20°C to +50° C Dimmable: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280lm 3000K material:Aluminum*Steel+plastic(ABS+PC) Color: gun grey New working modes! Image: Charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh,18650 LHon rechargeable battery Image: Content of delivery: Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749	
Dimmable: No Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280Im 3000K Immable: Control of the unit: Detailed construction: Weight of the unit: Detailed construction: USB-ccharge port, No USB cable Twillight sensor (Turn on at dusk only) With 1x 3.7V, 2000mAh, 18650 LHon rechargeable battery Off-level 0FF.Press +1 time. Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749	
Dimensions: 173x160x151(H)mm Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280Im 3000K Imaterial:Aluminum+Steel+plastic(ABS+PC) Color: gun grey New working modes! USB-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh,18650 LHon rechargeable battery OFF: Press +1 time. Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749	
Material: Plastic, Aluminum and steel Weight of the unit: 389g Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280Im 3000K material:Aluminum+Steel+plastic(ABS+PC) Color: gun grey New working modest USB-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh,18650 LHon rechargeable battery Indicator light red of Pres + time. Weight of delivery: Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: OFF. Press + time. EAN code: 4260663511749	
Weight of the unit: 389g Solar wall lamp IP44 with PIR Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280Im 3000K material:Aluminum+Steel+plastic(ABS+PC) Color: gun grey New working modes! USB-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh,18650 Li-ion rechargeable battery Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749	
Solar wall lamp IP44 with PIR black sensor, CRI95 LED module: 2.5W/280Im 3000K material:Aluminum+Steel+plastic(ABS+PC) Color: gun grey New working modes! USB-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh,18650 Li-lon rechargeable battery Imicator light red of the tradition sensor to the tradition sensor OFF: Press 11 time. Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749	
black sensor, CRI95 Off Figure 4 LED module: 2.5W/280im 3000K Off Figure 4 material:Aluminum-Steel+plastic(ABS+PC) Color: gun grey New working modes! USB-C charge port, No USB cable Twilight sensor (Turn on at dusk only) with 1x 3.7V, 2000mAh,18650 Li-ion rechargeable battery Off-Piezees with off sensor Off-Piezees with figure 4 Content of delivery: 1x Product, 2x fixing screws, 2x dowels, 1x mounting bracket, 1x Operation manual Package: Brown box with color sticker EAN code: 4260663511749	
Package: Brown box with color sticker EAN code: 4260663511749	w ON mixed w ON
EAN code: 4260663511749	
Outer carton size: 57X34.5X34CM	
Loading qty per export 12	
Product Warranty: 2 years	