

TYREinflate 2110



Large analogue pressure gauge

Easily monitor pressure from a distance for accurate inflation



3 m wind-up power cable

Pack up is easy and kink free with the smooth wind-up power cable



Large, powerful LED light to illuminate workspace

For inflating in dark conditions, the large LED light is designed to illuminate the work area ahead without the need to reposition the inflator



Powerful, precise, and easy tyre inflation

Introducing the OSRAM TYREinflate 2110, the combination of simplicity and power for hassle-free tyre inflation. This advanced inflator features a large, easy-to-read analogue pressure gauge, delivering precise pressure readings every time. The wind-up 3m 12V power cable allows for a quick and tidy pack-up, while the integrated valve storage post ensures valve caps stay secure during use.

Designed with convenience in mind, the 60cm inflation hose is neatly stored within the unit, and three versatile valve adaptors are safely housed inside, ready for a variety of inflation tasks. Large, intuitive buttons make operation effortless, and its powerful performance can inflate a 13" tyre in just 4 minutes.¹⁾²⁾

Compact, reliable, and user-friendly, the OSRAM TYREinflate 2110 is the solution for drivers who value precision and efficiency on the road.

Technical data

Product information

Inflation time	4.0 min
Max Pressure	6.9 bar
Air Hose Length	60 cm
Power Cord Length	3.0 m
Display Size	50 mm
Measuring Units	PSI, bar
Accuracy (bar)	±0.1 bar
Flow rate (l/min)	tbc

General Product Information

Global order reference	OTI2110
------------------------	---------

Electrical Data

Nominal wattage	120 W
Operating Voltage	12 V
Power Source	12 V DC

Physical Attributes & Dimensions



Length	220.0 mm
Width	105.0 mm
Height	152.0 mm

Operating Conditions

Noise Level (dB)	85 dB
------------------	-------

Additional product data

Product datasheet

Display Type	Analogue
Recommended to Use With	Motorbike, Car, Small Van

Capabilities

Accessories	Adaptors for: Balls, Air Mattress, Bikes
Fuse	10 A

Environmental & Regulatory Information



Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh)	
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	7fd425a7-0e8b-450d-96ad-7bff2ce486b7

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172411752	TYRE inflate 2110	Folding carton box 1	224 mm x 109 mm x 164 mm	4.00 dm ³	964.00 g
4062172411769	TYRE inflate 2110	Shipping carton box 4	350 mm x 232 mm x 244 mm	19.81 dm ³	4177.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	User instruction TYREinflate 2110

Legal advice

1)Based on inflating a 13" tyre from flat to 2.4 BAR

2)Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Product datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.