## Product Data Sheet

BOLI	Ð
	-

BOLD item code:	13827
Product name:	STROMVERSORGUNG 72W FÜR 24V OUTDOOR SYSTEM
Brand:	BOLD LIGHTING
Product picture:	with IP44 EU plug
Colour:	BLACK
Rated Input:	220-240VAC 50/60Hz, 0.5A MAX
Rated Output:	24V DC, 3.0A, 72W
Maximum output power:	Max. 72W
No-load power (Pno):	≤ 0,50W
Standby power (Psb):	N/A
Networked standby power (Pnet):	N/A
Energy efficiency in full-load(%):	86.50%
Intended use:	USE ONLY FOR LED MODULES!
IP protection degree:	IP67( for Driver); IP44 (for EU supply plug)
Safety protection class:	
Dimmable:	No, the control gear is not suitable for dimming of light sources.
Ambient Temperature ta:	Ta: 45°C;
Maximum Case Temperature tc:	Tc: 85°C (Measured on tc point indicated of the rating plate)
Operating temperature:	-25°C to 45°C
Material of housing:	Plactic(PC)
Outer dimensions:	129X56.1X38.5MM
Weight of the unit:	637g
Detailed specification:	IP67 Desktop driver:  1) Input: 220-240V~ 50/60Hz, 0.5A MAX; Output: 24V/DC, MAX.3A 72W  2) Input of driver: with H05RN-F 2x1.0mm² 1.5m rubber cable and IP44 EU plug  3) Output of driver: with H05RN-F 2x1.0mm² 15cm rubber cable + BOLD M18 female connector;  4) with 1-way conductive device with 0,5m cable(H05VV-F 2*1.0mm²) and BOLD's M18 male connector as accessory (to connenct with the output driver or output of 2.4G controller)  5) Driver size: 12.9x5.61x3.85cm  6) Black housing
Delivery Content:	1x IP67 Desktop driver 1x Trafo/Controller connector to system cable M18 1x instruction manual
Package:	Brown box with color sticker
EAN code:	4260663511282
Sale packaging size:	210x110x90mm
Outer carton size:	240x250x305mm
Loading qty per export carton:	6
Product Warranty:	2 years
Remarks:	