Product Data Sheet

ВО	Ш	D

Product picture: Stainless steel	OLD item code:	13567
Brand: BOLD LIGHTING Product picture: Stainless steel Coeration: As A DC Power consumption: Linkt colour: 3000K, Warm white Rendering Index(Ra): 80 Beam anole: 90° Luminous flux: 50lm (LED-Modul), 30lm (Whole light) Energy efficiency class: G Number of LEDs: 2 Housing material: Stainless steel Safety protection class: Class III Life time(L70850): 50000 h 1P protection degree: 1P67 Operating temperature: 25°C to 45°C Dimensions: 34.53'34.53'25.MM Installation cut-out (mm): 28 Dimmable: Weight of the unit: 101g IP65 LED Deck light: 1) Input: 24V DC Detailed construction: 9 (S) Material: Stainless steel body, glass diffuser 3) Light source 0.6W, 50lm, 3000K, Ra.80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 9 (Anti-order cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4106683511442 Sale packaging size: 110608080mm Outer carton size: 410x270x410mm Inner carton size: 10ading qty per inner carton: Loading	OLD Reill code.	
Product picture: Stainless steel Operation: 24V DC Power consumption: Max 0.6W Light colour: 3000K, Warm white Rendering Index(Ra): 80 Beam angle: 190° Luminous flux: 50lm (LED-Modul), 30lm (Whole light) Energy efficiency class: G Number of LEDs: 1 Housing material: Stainless steel Safety protection class: Class III Ufe time(L70850): 10 protection degree: 1P67 Departing temperature: 25°C to 45°C Dimensions: 34.5X34.5X32.5MM Installation out-out (mm): 26 Dimmable: yes, via the controller and remote control Weight of the unit: 101g Peb ELD Deck light: 1) Input 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4260663311442 Sale packaging size: 110x60x80mm Outer carton size: 410x270x410mm Inner carton size: 410x270x410mm Inner carton size: 410x270x410mm Inner carton size: 10ading qty per inner carton: 544 Loading qty per inner carton: 544	roddot ridirio.	
Description: 24V DC		
Deceration:	olour:	Stainless steel
Power consumption: Max.0.6W	I _c	24V DC
Light colour: 3000K, Warm white 80 80 8em anole: 90°	T,	Max.0.6W
Rendering Index(Ra): Beam anole: 90° Luminous flux: 50lm (LED-Modul), 30lm (Whole light) Enerov efficiency class: G Number of LEDs: 2 Housing material: Safety protection class: Life time(L70B50): 1P protection degree: 1P67 Operating temperature: -25°C to 45°C Dimensions: 34.5X34.5X32.5MM Installation cut-out (mm): Dimmable: yes, via the controller and remote control Weight of the unit: 101g 1P65 LED Deck light: 1) Input: 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light: 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x60x80mm Outer carton size: 410x270x410mm Inner carton size: 410x210x410x410mm Loading qty per inner carton: 54		3000K, Warm white
Beam anole: Luminous flux: Forerox efficiency class: G Number of LEDs: Life time(L70B50): Softon (LED-Modul), 30lm (Whole light) Stainless steel Safety protection class: Class III Life time(L70B50): Softon (Lede-Modul), 30lm (Whole light) Safety protection class: Class III Life time(L70B50): Softon (Lede-Modul), 30lm (Whole light) Life time(L70B50): Softon (Lede-Modul), 30lm (Whole light) Safety protection class: Class III Life time(L70B50): Softon (Lede-Modul), 30lm (Whole light) Life time(L70B50): Softon (Lede-Modul), 30lm (Whole light) Safety protection class: Life time(L70B50): Softon (Lede-Modul), 30lm (Whole light) Safety protection class: Life time(L70B50): Softon (Lede-Modul), 30lm (Whole light) Safety protection class: Life time(L70B50): Softon (Lede-Modul), 30lm (Whole light) Safety protection class: Ilea (Lede-Modul), 30lm (Whole light) Softon (Lede-Modul), 30lm (Whole light) Life time(L70B50): Softon (Lede-Modul), 30lm (Whole light) Life time(L70B50): Softon (Lede-Modul), 30lm (Whole light) Life time(L70B50): Softon (Lede-Modul), 30lm (Whole light) Log (Lede-Modul), 30lm (Lede-Modul)	l c	30
Luminous flux: 50lm (LED-Modul), 30lm (Whole light) Enerov efficiency class: G Number of LEDs: 2 Housing material: Stainless steel Safety protection class: Class III Life time(L70B50): 1P protection degree: Operating temperature: -25°C to 45°C Dimensions: 34 .5X34.5X32.5MM Installation cut-out (mm): 26 Dimmable: Weight of the unit: 101g Petailed construction: 1P65 LED Deck light: 1	endenna maexirta).	
Energy efficiency class: Solution Class	1,	50lm (LED-Modul) 30lm (Whole light)
Number of LEDs: 2	ummous nux.	, , , , , , , , , , , , , , , , , , , ,
Housing material: Stainless steel Safety protection class: Class III Life time(L70B50): Source time(L70B50): IP protection degree: Operating temperature: -25°C to 45°C Dimensions: 34.5X34.5X32.5MM Installation cut-out (mm): 26 Dimmable: yes, via the controller and remote control Weight of the unit: 101g IP65 LED Deck light: 1) Input: 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x6x80mm Outer carton size: 260x130x130mm Loading qty per inner carton: 6 Loading qty per inner carton: 54	nergy emclency class.	
Safety protection class: Class III Life time(L70B50): 50000 h IP protection degree: IP67 Operating temperature: -25°C to 45°C Dimensions: 34.5X34.5X32.5MM Installation cut-out (mm): 26 Dimmable: yes, via the controller and remote control Weight of the unit: 101g IP65 LED Deck light: 1) Input: 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x6x80mm Outer carton size: 260x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54	umber of LEDS.	
Life time(L70B50): 50000 h IP protection degree: IP67 Operating temperature: -25°C to 45°C Dimensions: 34.5X34.5X32.5MM Installation cut-out (mm): 26 Dimmable: yes, via the controller and remote control Weight of the unit: 101g IP65 LED Deck light: 1) Input: 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x60x80mm Outer carton size: 410x270x410mm Inner carton: 22 260x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54		
IP protection degree: IP67 Operating temperature: -25°C to 45°C Dimensions: 34.5X34.5X32.5MM Installation cut-out (mm): 26 Dimmable: yes, via the controller and remote control Weight of the unit: 101g IP65 LED Deck light: 1) Input: 24V DC 2.2 Material: Stainless steel body, glass diffuser 3.3 Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x60x80mm Outer carton size: 260x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54		
Operating temperature: -25°C to 45°C Dimensions: 34.5X34.5X32.5MM Installation cut-out (mm): 26 Dimmable: yes, via the controller and remote control Weight of the unit: 101g IP65 LED Deck light: 1) Input: 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x60x80mm Outer carton size: 410x270x410mm Inner carton size: 260x130x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54		
Dimensions: 34.5X34.5X32.5MM Installation cut-out (mm): 26 Dimmable: yes, via the controller and remote control Weight of the unit: 101g IP65 LED Deck light: 1) Input: 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x60x80mm Outer carton size: 260x130x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Installation cut-out (mm): Dimmable: yes, via the controller and remote control Weight of the unit: 101g IP65 LED Deck light: 1) Input: 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x60x80mm Outer carton size: 110x60x80mm Outer carton size: 260x130x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54		
Dimmable: yes, via the controller and remote control Weight of the unit: 101g IP65 LED Deck light: 1) Input: 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x60x80mm Outer carton size: 410x270x410mm Inner carton size: 260x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54		
Weight of the unit: 101g IP65 LED Deck light: 1) Input: 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x60x80mm Outer carton size: 410x270x410mm Inner carton size: 260x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54	stallation cut-out (mm): 2	26
IP65 LED Deck light: 1) Input: 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x60x80mm Outer carton size: 410x270x410mm Inner carton size: 260x130x130mm Loading qty per inner carton: 54	immable:	yes, via the controller and remote control
1) Input: 24V DC 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector 6) Anti-reverse design Content of delivery: 2x LED deck light 1x instruction manual Package: Brown box with color sticker EAN code: 426063511442 Sale packaging size: 410x270x410mm Outer carton size: 410x270x410mm Inner carton size: 260x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54	/eight of the unit:	101g
1x instruction manual Package: Brown box with color sticker EAN code: 4260663511442 Sale packaging size: 110x60x80mm Outer carton size: 410x270x410mm Inner carton size: 260x130x130xmm Loading qty per inner carton: 6 Loading qty per export carton: 54	etailed construction: 4	1) Input: 24V DC ² 2) Material: Stainless steel body, glass diffuser 3) Light source: 0.6W, 50lm, 3000K, Ra:80 4) Beam angle 90° 5) With input cable(cable length ca.15cm, H03VV-F 2X0.5mm², PVC) and M12 male connector
EAN code: 4260663511442 Sale packaging size: 110x60x80mm Outer carton size: 410x270x410mm Inner carton size: 260x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54	ontent of delivery:	2x LED deck light 1x instruction manual
Sale packaging size: 110x60x80mm Outer carton size: 410x270x410mm Inner carton size: 260x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54	ackage: E	Brown box with color sticker
Outer carton size: 410x270x410mm Inner carton size: 260x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54	AN code: 4	4260663511442
Inner carton size: 260x130x130mm Loading qty per inner carton: 6 Loading qty per export carton: 54	ale packaging size: 1	110x60x80mm
Loading qty per inner carton: 6 Loading qty per export carton: 54	uter carton size:	410x270x410mm
Loading qty per export carton: 54	ner carton size:	260x130x130mm
Loading qty per export carton: 54	oading qty per inner carton:	3
Product Worranty: 5 years		54
Frioductivalianty. 13 years	roduct Warranty:	5 years
Remarks: Only to be operated in conjuntion with a suitable power supply.	emarks:	Only to be operated in conjuntion with a suitable power supply.