



Designation IEC:

HR6

Size:.....

AA

Nominal Voltage:.....

1.2 V

Rated Capacity:.....

2100 mAh

Internal Resistance DC; fully charged:.....

45 mΩ

Impedance AC at 1 kHz; fully charged:.....

40 mΩ

Max. Discharge Current (continuous load / 0.8 V):.....

4.2 A

Typical Capacity at:

0.2 C / 1.0 V:.....

2100 mAh

1.0 C / 0.9 V:.....

1890 mAh

Charge Retention:

75 % of initial capacity after one year storage at 20 °C;
determined at 0.2 C discharge rate

Dimensions:

Diameter a:.....

14.5^{-1.0} mm

Height b:.....

50.5^{-1.3} mm

Shoulder Height c:.....

49.5^{-1.3} mm

Cap Diameter d:.....

5.5^{-1.3} mm

Volume:.....

8 cm³

Weight (approx.):.....

30 g

Charge Conditions at:

Standard Charge:.....

210 mA, 16 h

Fast Charge:.....

2100 mA (-dV)

Trickle Charge (0.03 - 0.05 C):.....

63 - 105 mA

Temperatures (recommended / permissible) at:

Storage:.....

-20 °C ... 25 °C / -20 °C ... 40 °C

Charge:.....

15 °C ... 30 °C / 0 °C ... 45 °C

Fast Charge:.....

15 °C ... 30 °C / 0 °C ... 40 °C

Discharge:.....

0 °C ... 40 °C / 0 °C ... 50 °C

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries